


# GCS-1500i

Green Communication System with Intel® Core™ i7/i5 rPGA988 Processor, 9 COM, 4 GbE, 8 USB2.0



## Features

- 1.5U 19" Rackmount, Fanless Design
- Intel® Core™ i7/i5 rPGA988, TDP 35W Max.
- Intel® QM57
- Dual-Channel DDR3 800/1066 Memory (Up to 8 GB)
- 10/100/1000Base-TX x 4
- VGA x 1, DVI-I x 1
- Serial Port With Isolation x 8, USB2.0 x 8, 8-Bit Digital I/O
- Internal 2.5" Disk Drive Bay x 1
- Wide Range 10~30V DC-In




## Specifications

CPU	Intel® Core™ i7/i5 rPGA988, max. TDP 35W	
Chipset	Intel® QM57	
System Memory	Up to 8 GB (DDR3 800/1066 MHz, SODIMM x 2)	
Display Interface	VGA	1
	DVI	1
	Others	—
Storage Device	SSD	Optional
	HDD	2.5" HDD x 1
Network	LAN	10/100/1000Base-TX x 4
	Wireless	—
Front I/O	USB Host	USB2.0 x 4
	LAN	—
	Serial Port	—
	DIO	—
	Audio	—
	KB/MS	—
	Others	—
Rear I/O	USB Host	USB2.0 x 4
	LAN	RJ-45 x 4
	Serial Port	COM x 9 (with isolation x 8)(RS-232/422/485)
	DIO	8-bit (4-in/4-out)
	Audio	—
	KB/MS	1
	Others	—
Expansion	PCIe	—
	PCI	—
	Mini card	—
	Mini PCI	—
	Others	—
Indicator	Front	HDD x 1, PWR x 1, LAN x 6, COM x 9
	Rear	—
Power Requirement	10~30V DC-In	
Power Consumption	Intel® Core™ i7-620M, 35W	
System Cooling	Passive Cooling	
Mounting	1.5U 19" Rackmount	
Operating Temperature	32°F ~ 113°F (0°C ~ 45°C)	
Storage Temperature	-4°F ~ 140°F (-20°C ~ 60°C)	
Anti-Vibration	1 g rms/ 5~500 Hz/ Operation	
Anti-Shock	30 G with 11 m/sec, Operation	
MTBF	30,500	

# GCS-1500i

## Dimension

Unit: mm



Certification	EMC	CE/FCC/Energy Star
	Safety	—
Dimension (W x H x D)	16.9" x 11.8" x 2.59" (430mm x 300mm x 60mm)	
Gross Weight	16.4lb (7.5Kg)	
Note	Windows® XP, Windows® 7, Linux Support	

## Packing List

- Product DVD
- GCS-1500i

## Ordering Information

- **TF-GCS-1500I-B10**  
Green Communication System, Intel® Core™ i7/i5, 9 COM, 4 Gigabit Ethernet, 8 USB, 10-30V DC, Rev. B1.0, with Isolation

## Optional Accessories

- **1757908401**  
(TF) Adapter, AC, 100/240V, 12V/7A, 84W, FSP, FSP 084-DMAA1
- **1702031802**  
(TF) AC Power Code, 3P-125V/10A 180D, 1.8M, USA
- **1702031803**  
(TF) AC Power Code, 3P-250V/10A 180D, 1.8M, Europe
- **170203180E**  
(TF) AC Power Code, 3P-125V/7A 180D, 1.8M, Japan