



New Product

Si1300BDL
Vishay Siliconix

N-Channel 20-V (D-S) MOSFET






RoHS
COMPLIANT

PRODUCT SUMMARY			
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A) ^a	Q_g (Typ)
20	0.85 at $V_{GS} = 4.5$ V	0.4	335
	1.08 at $V_{GS} = 2.5$ V	0.35	

FEATURES

- TrenchFET[®] Power MOSFET
- 100 % R_g Tested



Ordering Information: Si1300BDL-T1-E3

N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_A = 25$ °C UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	20	V
Gate-Source Voltage		V_{GS}	± 8	
Continuous Drain Current ($T_J = 150$ °C)	$T_C = 25$ °C	I_D	0.4	A
	$T_C = 70$ °C		0.32	
	$T_A = 25$ °C		0.37 ^{b, c}	
	$T_A = 70$ °C		0.30 ^{b, c}	
Pulsed Drain Current		I_{DM}	0.5	
Continuous Source-Drain Diode Current	$T_C = 25$ °C	I_S	0.18	
	$T_A = 25$ °C		0.14 ^{b, c}	
Maximum Power Dissipation	$T_C = 25$ °C	P_D	0.2	W
	$T_C = 70$ °C		0.14	
	$T_A = 25$ °C		0.19	
	$T_A = 70$ °C		0.12 ^{b, c}	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150	°C

THERMAL RESISTANCE RATINGS					
Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^{b, d}	$t \leq 5$ sec	R_{thJA}	540	670	°C/W
Maximum Junction-to-Foot (Drain)	Steady State	R_{thJF}	450	570	

Notes:

- Based on $T_C = 25$ °C.
- Surface mounted on 1" x 1" FR4 board.
- $t = 5$ sec
- Maximum under steady state conditions is 360 °C/W.

SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{DS}	V _{GS} = 0 V, I _D = 250 μA	20			V
V _{DS} Temperature Coefficient	ΔV _{DS} /T _J	I _D = 250 μA		20		mV/°C
V _{GS(th)} Temperature Coefficient	ΔV _{GS(th)} /T _J			-2.8		
Gate-Source Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	0.4		1.0	V
Gate-Source Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±8 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 20 V, V _{GS} = 0 V			100	nA
		V _{DS} = 20 V, V _{GS} = 0 V, T _J = 55 °C			5	μA
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 4.5 V	0.4			A
		V _{DS} ≥ 5 V, V _{GS} = 2.5 V	0.12			
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = 4.5 V, I _D = 0.25		0.65	0.85	Ω
		V _{GS} = 2.5 V, I _D = 0.15		0.85	1.08	
Dynamic^b						
Input Capacitance	C _{iss}	V _{DS} = 10 V, V _{GS} = 0 V, f = 1 MHz		35		pF
Output Capacitance	C _{oss}			13		
Reverse Transfer Capacitance	C _{rss}			4		
Total Gate Charge	Q _g	V _{DS} = 10 V, V _{GS} = 4.5 V, I _D = 0.4		560	840	pC
		V _{DS} = 10 V, V _{GS} = 2.5 V, I _D = 0.35		335	503	
Gate-Source Charge	Q _{gs}			98		
Gate-Drain Charge	Q _{gd}		85			
Gate Resistance	R _g	f = 1 MHz		7	12	Ω
Turn-On Delay Time	t _{d(on)}	V _{DD} = 10 V, R _L = 25 Ω I _D = 0.4 A, V _{GEN} = 4.5 V, R _g = 1 Ω		7	12	ns
Rise Time	t _r			10	15	
Turn-Off Delay Time	t _{d(off)}			8	13	
Fall Time	t _f			7	12	
Drain-Source Body Diode Characteristics						
Continuous Source-Drain Diode Current	I _S	T _C = 25 °C			0.18	A
Pulse Diode Forward Current ^a	I _{SM}				0.4	
Body Diode Voltage	V _{SD}	I _S = 0.05 A		0.7	1.2	V

Notes


- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2 %.
b. Guaranteed by design, not subject to production testing.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.




TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)


Output Characteristics




Transfer Characteristics curves vs. Temp




On-Resistance vs. Drain Current




Capacitance



Qg - Gate Charge








On-Resistance vs. Junction Temperature







TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)



* $V_{GS} >$ minimum V_{GS} at which $r_{DS(on)}$ is specified



TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)



*The power dissipation P_D is based on $T_{J(max)} = 150 \text{ }^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?73557>.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.