Product data sheet
Characteristics

CHU364AWK
200A 3P Type12 600VAC/DC Heavy Duty Non-Fusible Safety Switch

Product availability : Stock - Normally stocked in distribution facility

Price* : 1,686.00 USD



Main

Product	Single Throw Safety Switch
Disconnect Type	Non-fusible disconnect
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty

Complementary

Line Rated Current	200 A
Factory Installed Neutral	None
Mounting Type	Surface
Voltage Rating	600 V AC/DC
Maximum Horse Power Rating	15 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 60 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 480 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 125 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 600 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 150 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC 50 hp 600 V at DC
Wire Size	AWG 6...250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.02…0.20 in² (13.30…127 mm²) AWG 6...250 kcmil)
Height	29 in (736.60 mm)
Width	18.63 in (473.20 mm)
Depth	8.75 in (222.25 mm)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Certifications	CSA
Enclosure Rating	NEMA 3R/12 galvannealed steel

Ordering and shipping details

Category	00153 - C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	00785901994657
Nbr. of units in pkg.	1
Package weight(Lbs)	52.6 lb(US) (23.86 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	9.80 in (24.892 cm)
Package 1 width	19.40 in (49.276 cm)
Package 1 Length	32.20 in (81.788 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes