KS-2438D

Double Sided Adhesive

pro-POWER



Description:

Construction : Release film, premier, adhesive, substrate material
Premier coating, adhesive : American dow corning silicone adhesive
Substrate material : Polyimide
Feature : Pressure-sensitive adhesive, no remaining adhesive, antistatic, heat-resist, anti corrosion

Specification Table

No.	Item	Unit	Specification
1	Release Film Thickness	mm	0.05 ±0.002
2	Substrate Material Thick	mm	0.025 ±0.002
3	Total Thickness	mm	0.15 ±0.008
4	Adhesion	Work Side N / 25 mm	5.8 - 7.6
		Adhesive Side N / 25 mm	6.5 - 8.3
6	Continuous Strength	H	≥ 24
7	Tensile Strength	N / 25 mm	≥ 85
8	Heat - Resist	°C / 5 min	280
9	Length	M	33
10	Width	mm	3 - 500
11	Colour	-	Brown
12	Storage, Handling	Storage must be in a dry, non-corrosive and shine environment	
13	Shelf Life	Shelf life is 2 years from data of manufacture	

Part Number Table

Description	Part Number
Tape, Kapton, Brown, 6 mm × 33 M	PPC226
Tape, Kapton, Brown, 9 mm × 33 M	PPC227
Tape, Kapton, Brown, 12 mm × 33 M	PPC228
Tape, Kapton, Brown, 19 mm × 33 M	PPC229
Tape, Kapton, Brown, 25 mm × 33 M	PPC230

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2011.