Microsemi LAWRENCE

TECHNICAL DATA

NPN POWER SILICON TRANSISTOR

Qualified per MIL-PRF-19500/544

Devices		*Qualified Level*
2N5152	**2N5154**	**JAN**
2N5152L	**2N5154L**	**JANTX**
		JANTXV

MAXIMUM RATINGS

Ratings	Symbol	All Units	Units
Collector-Emitter Voltage	V_{CEO}	80	Vdc
Collector-Base Voltage	V_{CBO}	100	Vdc
Emitter-Base Voltage	V_{EBO}	5.5	Vdc
Collector Current	I_C (3, 4)	2.0	Adc
Total Power Dissipation @ $T_A = +25^0C$ (1) @ $T_C = +25^0C$ (2)	P_T	1.0 11.8	W W
Operating & Storage Temperature Range	T_j, T_{stg}	-65 to +200	°C


THERMAL CHARACTERISTICS

Characteristics	Symbol	Max.	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	15	$^0C/W$

1) Derate linearly 5.7 mW/^{0}C for $T_A > +25^0C$
2) Derate linearly 66.7 mW/^{0}C for $T_C > +25^0C$
3) Derate linearly 80 mW/^{0}C for $T_C > +25^0C$
4) This value applies for $P_W \leq 8.3$ ms, duty cycle ≤ 1%



TO- 5*
2N5152L, 2N5154L



2N5152, 2N5154
TO-39*
(TO-205AD)

*See appendix A for package outline

ELECTRICAL CHARACTERISTICS ($T_A = 25^0C$ unless otherwise noted)

Characteristics	Symbol	Min.	Max.	Unit
OFF CHARACTERISTICS				
Collector-Emitter Breakdown Voltage I_C = 100 mAdc, I_B = 0	$V_{(BR)CEO}$	80		Vdc
Emitter-Base Cutoff Current V_{EB} = 4.0 Vdc, I_C = 0 V_{EB} = 5.5 Vdc, I_C = 0	I_{EBO}		1.0 1.0	µAdc mAdc
Collector-Emitter Cutoff Current V_{CE} = 60 Vdc, V_{BE} = 0 V_{CE} = 100 Vdc, V_{BE} = 0	I_{CES}		1.0 1.0	µAdc mAdc
Collector-Base Cutoff Current V_{CE} = 40 Vdc, I_B = 0	I_{CEO}		50	µAdc

ELECTRICAL CHARACTERISTICS (con't)

Characteristics		Symbol	Min.	Max.	Unit
ON CHARACTERISTICS					
Forward Current Transfer Ratio					
I_C = 50 mAdc, V_{CE} = 5 Vdc	2N5152		20		
	2N5154		50		
I_C = 2.5 Adc, V_{CE} = 5 Vdc					
	2N5152	h_{FE}	30	90	
	2N5154		70	200	
I_C = 5 Adc, V_{CE} = 5 Vdc					
	2N5152		20		
	2N5154		40		
Collector-Emitter Saturation Voltage					
V_{CE} = 5 Vdc, I_C = 2.5 Adc		$V_{CE(sat)}$		0.75	Vdc
I_C = 5 Adc, I_B = 500 Adc				1.5	
Base-Emitter Voltage non-saturated					
I_C = 2.5 Adc, I_B = 250 mAdc		V_{BE}		1.45	Vdc
I_C = 5 Adc, I_B = 500 mAdc					
Base-Emitter Saturation Voltage					
I_C = 2.5 Adc, I_B = 250 mAdc		$V_{BE(sat)}$		1.45	Vdc
I_C = 5 Adc, I_B = 500 mAdc				2.2	
DYNAMIC CHARACTERISTICS					
Magnitude of Common Emitter Small-Signal Short Circuit Forward-Current Transfer Ratio					
I_C = 500 mAdc, V_{CE} = 5 Vdc, f = 10 MHz	2N5152	$\lvert h_{fe} \rvert$	6		
	2N5154		7		
Small-Signal Short Circuit Forward-Current Transfer Ratio					
I_C = 100 mAdc, V_{CE} = 5 Vdc, f = 1 kHz	2N5152	h_{fe}	20		
	2N5154		50		
Output Capacitance					
V_{CB} = 10 Vdc, I_E = 0, f = 1.0 MHz		C_{obo}		250	pF

SWITCHING CHARACTERISTICS

Turn-On Time					
I_C = 5 Adc, I_{B1}= 500 mAdc		t_{on}		0.5	µs
Turn-Off Time					
R_L = 6Ω		t_{off}		1.5	µs
Storage Time	I_{B2}= -500 mAdc	t_s		1.4	µs
Fall Time	$V_{BE(OFF)}$ = 3.7 Vdc	t_f		0.5	µs

SAFE OPERATING AREA

DC Tests

T_C = +25^{0}C, 1 Cycle, t_p= 1.0 s

Test 1

V_{CE} = 5.8Vdc, I_C = 2.0 Adc

Test 2

V_{CE} = 32 Vdc, I_C = 340 mAdc

Test 3

V_{CE} = 80 Vdc, I_C = 20 mAdc