LT–LED LT–LED MV and LT–LED 110/230V



Mains 110/230V	amber >6cd red >10cd	65 flashes/min 6 bursts/flash	85–265 Vac	IP67	148gms
Multivoltage MV			10–100Vdc		

CE – certified to EMC directive 2004/108/EC.
Complies with low voltage directive 2006/95/EC.
High voltage transient and polarity reversal protected.
Operating temperature: –20ºC to + 55ºC.

Features:

A compact LED beacon with low power consumption.


- Multivoltage 10–100Vdc, and mains 110Vac and 230Vac versions
- Flashing and continuously lit modes
- Clear lens with coloured LEDs
- Low power consumption
- 3 year guarantee
- Weatherproof to IP67

Materials:

Polycarbonate lens and base. ROHS compliant.

Accessories:

FX2
mounting
base




FX40
mounting
bracket




FX39
mounting
pole



Product	*i* flashing	*i* constant	Amber	Red
Mains 110/230V	15mA @ 110Vac 10mA @ 230Vac		448002	448003
Multivoltage MV	110mA @ 12Vdc 55mA @ 24Vdc 35mA @ 50Vac 25mA @ 100Vac	80mA @ 12Vdc 40mA @ 24Vdc 25mA @ 50Vac 20mA @ 100Vac	446002	446003





delta design
ADVANCED WARNING TECHNOLOGY...
Primrose Hill, Kings Langley, Herts WD4 8ST, England.
Tel: (U.K.) 01923 272850 (Int.) +44 1923 272850 • Fax: (U.K.) 01923 260167 (Int.) +44 1923 260167 • E-mail: sales@deltadesign.co.uk • Web: www.deltadesign.co.uk