

HWS300-24/PV





Sales Region	Worldwide
Series	HWS
Status	Production
Feature	
Option	Output voltage can be controlled by external voltage
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics		
Input Voltage Range[AC]	85 to 265V	
Input Voltage Range[DC]	120 to 330V	
Efficiency	85% Typ.	
Rated Output Voltage[DC]	24V	
Output Voltage Range[DC]	19.2 to 28.8V	
Maximum Output Current	14A	
Maximum Average Current		
Maximum Peak Current	16.5A	
Maximum Output Power	336W	
Maximum Average Power		
Maximum Peak Power		

Cases Shape & Size		
Case' shape	Unit	
Width(W)	61mm Nom.	
Height(H)	82mm Nom.	
Depth(D)	165mm Nom.	
Weight	1000g Typ.	

Other		
Operating Temp. Range	-10 to 70°C	
Cooling	Blower fan cooling	
	UL60950-1	
	CSA C22.2 No.60950-1	
Safety Standard(Certified)	CSA C22.2 No.14-M95	
Salety Standard(Certified)	EN60950-1	
	UL508	
	EN50178	
Safety Standard(Conformed)	Den-an	

[!] Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.