


P.C.B LAYOUT  
TOP VIEW

1. CONTACT CURRENT RATING: 1A.
2. CONTACT RESISTANCE: 30 mΩ MAX.;
3. INSULATION RESISTANCE: 100MΩ MIN.;
4. DIELECTRIC WITHSTANDING: 500V AC MIN.;
5. DURABILITY: 5,000 CYCLES MIN.;
6. CONNECTOR MATING FORCES: 30N MAX.;
7. CONNECTOR UNMATING FORCES: 3N MIN.;

②	Shunt terminal	6	Phosphor bronze	Plating Au		
①	Housing	1	PA	Black		
ITEM	PART NAME	Serial number	QTY.	MATERIAL	FINISHING	REMARK

DRAWN	QIFENG.XU	2014/12/19	TITLE:	PHONE JACKES
CHECKED				
APPROVALS			PART NO.	PJ-332D
TOLERANCES ARE			SCALE:	1:1
30~0.1	±0.30	ANGLE	UNIT:	mm
10~0.30	±0.20	±2'	DRAWING NO.	
5~10	±0.15			
~5	±0.10			



ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
ELECTRONICS CO.,LTD						
SHEET 1 OF 1						