


FM4001-M thru FM4007-M

SURFACE MOUNT STANDARD RECOVERY RECTIFIER

VOLTAGE - 50 TO 1000 VOLTS CURRENT - 1.0 AMPERES



FEATURES

- Plastic package has Underwriters Laboratory
- Flammability Classification 94V-0 Uzifzing Flame
- Retardant Epoxy Molding Compound.
- For surface mounted applications.
- Exceeds environmental standards of ML-S-19500/228
- Low leakage current

MECHANICAL DATA

Case : JEDEC SOD-123/MINI-SMA molded plastic
 Terminals : Solder plated, solderable per
 MIL-STD-750, Method 2026
 Polarity : Indicated by cathode band
 Mounting Position : Any
 Weight : 0.04gram

MAXIMUM RATINGS (at $T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	Min.	Typ.	Max.	UNITS
Forward rectified current	See Fig.2	I_o			1.0	A
Forward surge current	8.3ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}			30	A
Reverse current	$V_R=V_{RRM}$ $T_A=25^\circ\text{C}$	I_r			5.0	μA
	$V_R=V_{RRM}$ $T_A=100^\circ\text{C}$				50	μA
Thermal resistance	Junction to ambient	$R_{\theta JA}$		60		$^\circ\text{C} / \text{W}$
	Junction to case	$R_{\theta JC}$		30		
Diode junction capacitance	F=1MHz and applied 4vDC reverse voltage	C_j		15		pF
Storage temperature		T_{STG}	-55		+150	$^\circ\text{C}$

SYMBOLS	MARKING CODE	V_{RRM}^{*1} (V)	V_{RMS}^{*2} (V)	V_R^{*3} (V)	V_F^{*4} (V)	Operating Temperature ($^\circ\text{C}$)
FM4001-M	A1	50	35	50	1.1	-55 to + 125
FM4002-M	A2	100	70	100		
FM4003-M	A3	200	140	200		
FM4004-M	A4	400	280	400		
FM4005-M	A5	600	420	600		
FM4006-M	A6	800	560	800		
FM4007-M	A7	1000	700	1000		

- *1 Repetitive peak reverse peak reverse
 *2 RMS voltage
 *3 Continuous reverse voltage
 *4 Maximum forward voltage

FM4001-M thru FM4007-M

SURFACE MOUNT STANDARD RECOVERY RECTIFIER

RATING AND CHARACTERISTICS CURVES FM4001-M THRU FM4007-M

FIG.1-TYPICAL FORWARD CHARACTERISTICS




FIG.2-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.4-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3 - TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

