

Han 16HP Direct/EMC-HSE-M32



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 19 39 816 0547 |
| Specification | Han 16HP Direct/EMC-HSE-M32 |
| HARTING eCatalogue | https://b2b.harting.com/19398160547 |

Identification

| | |
|--------------------------|--------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han® HP Direct EMC |
| Type of hood/housing | Hood |

Version

| | |
|--------------|---------------|
| Locking type | Screw locking |
| Size | 16 B |
| Version | Side entry |
| Cable entry | 1x M32 |

Technical characteristics

| | |
|--|--|
| Tightening torque (screw locking) | 4 Nm |
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP66 IP68 IP69 / IPX9K acc. to ISO 20653 |

Material properties

| | |
|-------------------------|-----------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Electrical conductive |
| Colour (hood/housing) | Unpainted |
| Material (seal) | NBR |
| Material (locking) | Stainless steel |
| RoHS | compliant |



Pushing Performance

Material properties

| | |
|-----------------------------|-----------|
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|----------------|-------------------------|
| Specifications | EN 60664-1 IEC 61984 |
| CE | Yes |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 329.5 g |
| Country of origin | China |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |