


3P~16P Shape
Scale 1:1



2P Shape
Scale 1:1

Specifications:

规格:
 Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating:3A AC/DC
 额定电流: 3A AC/DC
 Withstanding voltage:1000V AC/minute
 耐受电压: 1000V AC/分钟
 Temperature range:-25℃~+85℃
 温度范围: -25℃~+85℃
 Insulation resistance:≥1000MΩ
 绝缘电阻: ≥1000MΩ
 Contact resistance:≤30mΩ
 接触电阻: ≤30mΩ
 After environmental testing:≤40mΩ
 环境测试后: ≤40兆欧

X2011 H X-XX A-N0 XX XX

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- 1.Series No
- 2.Category:H-HSG
- 3.Appearance type:Blank-Ordinary
- 4.Row No-Pin No:XX-02P~16P
- 5.Plug the Pin&Special N0:A-With Lock
- 6.Material:N0-PA66 UL 94V-0
- 7.Color:Blank-Natural Color
BK-Black
- 8.Whether containing halogen:
HF-Halogen free
Blank-Containing halogen

poles	Dimensions(mm)			poles	Dimensions(mm)		
	A	B	C		A	B	C
2	2.00	5.60	4.60	10	18.00	21.60	20.60
3	4.00	7.60	6.60	11	20.00	23.60	22.60
4	6.00	9.60	8.60	12	22.00	25.60	24.60
5	8.00	11.60	10.60	13	24.00	27.60	26.60
6	10.00	13.60	12.60	14	26.00	29.60	28.60
7	12.00	15.60	14.60	15	28.00	31.60	30.60
8	14.00	17.60	16.60	16	30.00	33.60	32.60
9	16.00	19.60	18.60				

X2011H-XXA-N0BK	PA66 UL 94V-0 Black	X2011T-A	X2011W-A
X2011H-XXA-N0	PA66 UL 94V-0		
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal



广东星坤科技股份有限公司

生	日期
效	
文件	工程
章	

REVISIONS

units:	mm
tolerance:	
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm

UNSPECIFIED TOLERANCES

DSND		DATE		SCALE: N/A	MODEL TYPE: Wire to board connector	
DWN		DATE		VIEW:	PART NO.:	
CHKD		DATE		UNIT: mm/in	2.00mm Crimp Style Connectors	
APPD		DATE		SIZE: A4	DWG NO.: X2011H-XXA-N0	
XKB INDUSTRIAL DECISION CO. LIMITED				WEIGHT	SHEET	REVISION