

THYRISTOR MODULE

PK(PD,PE)200HB

UL:E76102 (M)

Power Thyristor/Diode Module **PK200HB** series are designed for various rectifier circuits and power controls. For your circuit application. following internal connections and wide voltage ratings up to 1,600V are available.



Isolated mounting base

- $I_T(AV)$ 200A, $I_T(RMS)$ 310A, I_{TSM} 5500A
- di/dt 200 A/ μ s
- dv/dt 500V/ μ s

(Applications)

Various rectifiers
AC/DC motor drives
Heater controls
Light dimmers
Static switches

Internal Configurations



Unit : mm

Maximum Ratings

Symbol	Item	Ratings		Unit
		PK200HB120 PE200HB120	PD200HB120 PE200HB160	
V_{RRM}	* Repetitive Peak Reverse Voltage	1200	1600	V
V_{RSM}	* Non-Repetitive Peak Reverse Voltage	1300	1700	V
V_{DRM}	Repetitive Peak Off-State Voltage	1200	1600	V

Symbol	Item	Conditions	Ratings	Unit
$I_T(AV)$	* Average On-State Current	Single phase, half wave, 180° conduction, $T_c : 74^\circ C$	200	A
$I_T(RMS)$	* R.M.S. On-State Current	Single phase, half wave, 180° conduction, $T_c : 74^\circ C$	310	A
I_{TSM}	* Surge On-State Current	$\frac{1}{2}$ cycle, 50Hz/60Hz, peak Value, non-repetitive	5000/5500	A
I^2t	* I^2t	Value for one cycle of surge current	125000	A ² S
P_{GM}	Peak Gate Power Dissipation		10	W
$P_{G(AV)}$	Average Gate Power Dissipation		3	W
I_{FGM}	Peak Gate Current		3	A
V_{FGM}	Peak Gate Voltage (Forward)		10	V
V_{RGM}	Peak Gate Voltage (Reverse)		5	V
di/dt	Critical Rate of Rise of On-State Current	$I_G=100mA$, $T_j=25^\circ C$, $V_D=\frac{1}{2}V_{DRM}$, $dI_G/dt=0.1A/\mu s$	200	A/ μs
V_{ISO}	* Isolation Breakdown Voltage (R.M.S.)	A.C. 1 minute	2500	V
T_j	* Operating Junction Temperature		-40 to +125	°C
T_{stg}	* Storage Temperature		-40 to +125	°C
	Mounting Torque	Mounting (M5)	Recommended Value 1.5-2.5 (15-25)	N·m (kgf·cm)
		Terminal (M8)	Recommended Value 8.8-10 (90-105)	
	Mass	Typical Value	510	g

Electrical Characteristics

Symbol	Item	Conditions	Ratings	Unit
I_{DRM}	Repetitive Peak Off-State Current, max.	at V_{DRM} , Single phase, half wave, $T_j=125^\circ C$	50	mA
I_{RRM}	* Repetitive Peak Reverse Current, max.	at V_{DRM} , Single phase, half wave, $T_j=125^\circ C$	50	mA
V_{TM}	* Peak On-State Voltage, max.	On-State Current 750A, $T_j=125^\circ C$ Inst. measurement	1.50	V
I_{GT}/V_{GT}	Gate Trigger Current/Voltage, max.	$T_j=25^\circ C$, $I_T=1A$, $V_D=6V$	100/3	mA/V
V_{GD}	Non-Trigger Gate, Voltage. min.	$T_j=125^\circ C$, $V_D=\frac{1}{2}V_{DRM}$	0.25	V
t_{gt}	Turn On Time, max.	$I_T=250A$, $I_G=100mA$, $T_j=25^\circ C$, $V_D=\frac{1}{2}V_{DRM}$, $dI_G/dt=0.1A/\mu s$	10	μs
dv/dt	Critical Rate of Rise of Off-State Voltage, min.	$T_j=125^\circ C$, $V_D=\frac{2}{3}V_{DRM}$, Exponential wave.	500	V/ μs
I_H	Holding Current, typ.	$T_j=25^\circ C$	50	mA
I_L	Latching Current, typ.	$T_j=25^\circ C$	100	mA
$R_{th}(j-c)$	* Thermal Impedance, max.	Junction to case	0.18	°C/W

* mark : Thyristor and Diode part. No mark : Thyristor part

