General Cable

Product Data Sheet

RoHS Compliant Directive 2002/95/EC

Part Number: C1228A Revision: 1/8/2013

2C 24ga Polypropylene, Shielded, PVC **AUDIO/VIDEO AND HOME ENTERTAINMENT**

A. CONSTRUCTION

		DIAMETERS
Conductor:	#24 AWG (19/36) Tinned Copper	.025" Nom
Insulation:	.008" Wall, Polypropylene (PP)	.041" Nom
Pair:	2C @ 1.50" LHL	
Shield:	Conductive Tape Aluminum/Polyester Tape, foil in, in contact with drain.	.093" Nom
Drain Wire:	#24 AWG (7/32) Tinned Copper	
Jacket:	.021" Wall, Polyvinyl Chloride (PVC)	.135" Nom
Print Legend:	***CAROL C1228A MADE IN USA***	

B. INDUSTRY APPROVALS

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +75°C
Suggested Working Voltage:	300V Max
Conductor DCR:	23 Ohms/1000 ft @ 20°C (nom)
Shield Resistance:	27 Ohms/1000 ft @ 20°C (nom)
Mutual Capacitance:	27pF/ft @ 1kHz (nom)
Ground Capacitance:	48 pF/ft @ 1kHz (nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED

E. CUSTOMER APPROVAL

Signature: _____

Date: _____

Note: Data subject to change without notice. Contact your Customer Service representative for latest information.