


Features

- Glass Passivated Die Construction
- Low leakage
- Ideal for printed circuit board
- Surge overload rating-30A peak
- Designed for Surface Mount Application
- Plastic Material-UL Flammability 94V-0

Mechanical Data

- Case:Reliable low cost construction utilizing molded plastic technique
- Terminals:Plated Leads Solderable per MIL-STD-202,Method208
- Polarity:As Marked on Case
- Mounting Position:Any
- Marking:Type Number



Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single Phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

TYPE NUMBER	SYMBOL	RMB1S	RMB2S	RMB4S	RMB6S	RMB8S	RMB10S	UNITS
Peak Repetitive Reverse Voltage	V _{RRM}	100	200	400	600	800	1000	V
Working Peak Reverse Voltage	V _{RWM}							
DC Blocking Voltage	V _{DC}							
RMS Reverse Voltage	V _{RMS}	70	140	280	420	560	700	V
Average Rectified Output Current (Note 1)@T _C =100℃ (Note 2)@T _C =100℃	I _{F(AV)}	0.5 0.8						A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	30						A
I ² t Rating for Fusing (t < 8.3ms)	I ² t	3.735						A ² s
Forward Voltage per element @I _F =0.8A	V _{FM}	1.3						V
Peak Reverse Current @T _A =25℃ At Rated DC Blocking Voltage @T _A =125℃	I _R	5.0 200						uA
Maximum reverse recovery time (Note 3)	T _{RR}	150			250	500		ns
Typical Junction Capacitance per leg (Note 4)	C _J	13						pF
Typical Thermal Resistance per leg	R _{θJA}	60						℃/W
	R _{θJL}	16						
Operating and Storage Temperature Range	T _J , T _{STG}	-55to+150						℃

Note:1. Mounted on glass epoxy PC board with 1.3mm² solder pad.

2. Mounted on aluminum substrate PC board with 1.3mm² solder pad.

3. Reverse Recovery Test Conditions: I_F=0.5A, I_R=1A, I_{rr}=0.25A.

4. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.

RMB1S THRU RMB10S









FIG.6 MOUNTING PAD LAYOUT



Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from DIYI.
- DIYI reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- DIYI disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- DIYI does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications.
DIYI makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown here in are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify DIYI for any damages resulting from such improper use or sale.
- Since DIYI uses lot number as the tracking base, please provide the lot number for tracking when complaining.