





440-073 EMI/RFI Banding Adapter Rotatable Coupling - Full Radius Profile

CONNECTOR DESIGNATORS A-F-H-L-S ROTATABLE COUPLING

Product Series — **440**
 Connector Designator — **F**
 Angle and Profile — **N**
 M = 45°
 N = 90°
 See page 440-44 for straight
 Basic Part No. — **073**
 NF
 16
 12
 K
 P
 Polysulfide (Omit for none)
 B = Band
 K = Precoiled Band (Omit for none)
 Cable Entry (Table IV)
 Shell Size (Table I)
 Finish (Table II)



STYLE 2
(See Note 1)



Band Option
(K Option Shown - See Note 3)

See inside back cover fold-out or pages 13 and 14 for Tables I and II.

TABLE III: ELBOW DIMENSIONS

Shell Size Conn. Desig. A-F-L-S	H	E Max	F Max	G Max	H Max
08	09	.812 (20.6)	.807 (20.5)	1.125 (28.6)	1.125 (28.6)
10	11	.875 (22.2)	.861 (21.9)	1.250 (31.8)	1.250 (31.8)
12	13	.938 (23.8)	.911 (23.1)	1.375 (34.9)	1.375 (34.9)
14	15	1.000 (25.4)	.965 (24.5)	1.500 (38.1)	1.500 (38.1)
16	17	1.062 (27.0)	1.014 (25.8)	1.625 (41.3)	1.625 (41.3)
18	19	1.094 (27.8)	1.064 (27.0)	1.750 (44.5)	1.750 (44.5)
20	21	1.156 (29.4)	1.118 (28.4)	1.875 (47.6)	1.875 (47.6)
22	23	1.188 (30.2)	1.172 (29.8)	2.000 (50.8)	2.000 (50.8)
24	25	1.250 (31.8)	1.221 (31.0)	2.125 (54.0)	2.125 (54.0)

TABLE IV: CABLE ENTRY

Dash No.	J Dia	K Dia
02	.125 (3.2)	.250 (6.4)
03	.188 (4.8)	.312 (7.9)
04	.250 (6.4)	.375 (9.5)
05	.312 (7.9)	.438 (11.1)
06	.375 (9.5)	.500 (12.7)
07	.438 (11.1)	.562 (14.3)
08	.500 (12.7)	.625 (15.9)
09	.562 (14.3)	.688 (17.5)
10	.625 (15.9)	.750 (19.1)
11	.688 (17.5)	.812 (20.6)
12	.750 (19.1)	.875 (22.2)
13	.812 (20.6)	.938 (23.8)
14	.875 (22.2)	1.000 (25.4)
15	.938 (23.8)	1.062 (27.0)
16	1.000 (25.4)	1.125 (28.6)
17	1.062 (27.0)	1.188 (30.2)
18	1.125 (28.6)	1.250 (31.8)
20	1.250 (31.8)	1.375 (34.9)
22	1.375 (34.9)	1.500 (38.1)
24	1.500 (38.1)	1.625 (41.3)

1. When maximum cable entry (page 21) is exceeded, Style 2 will be supplied. Dimensions E, F, G and H will not apply. Please consult factory.
2. Metric dimensions (mm) are indicated in parentheses.
3. Backshells supplied with 600-052-* band, see Glenair Series 600 Tool Catalog for installation.