SIYU®


SFAF502G SFAF508G

塑封超快速整流二极管

反向电压 100---600V
正向电流 5.0A

Plastic Ultra-Fast Recover Rectifier

Reverse Voltage 100 to 600 V
Forward Current 5.0 A



特征 Features

- 大电流承受能力。High Current Capability
- 正向压降低。Low Forward Voltage Drop
- 低功耗高效率。Low Power Loss，High Efficiency
- 引线和管体皆符合RoHS标准 。
  Lead and body according with RoHS standard

机械数据 Mechanical Data

·封装: 塑料封装 Case: Molded Plastic

·极性: 标记模压或印于本体 Polarity: Symbols molded or marked on body

·安装位置: 任意 Mounting Position: Any

·安装扭距: 推荐值 0.3牛*米 Mounting torque：Recommend 0.3 N*m

极限值和温度特性 TA = 25℃ 除非另有规定。

Maximum Ratings & Thermal Characteristics Ratings at 25℃ ambient temperature unless otherwise specified.

	符号 Symbols	SFAF502G	SFAF504G	SFAF506G	SFAF508G	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V_{RRM}	100	200	400	600	V
最大均方根电压 Maximum RMS voltage	V_{RMS}	70	140	280	420	V
最大直流阻断电压 Maximum DC blocking voltage	V_{DC}	100	200	400	600	V
最大正向平均整流电流 Maximum average forward rectified current	$I_{F(AV)}$	5.0				A
峰值正向浪涌电流 8.3ms单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I_{FSM}	125				A
典型热阻 Typical thermal resistance	$R_{\theta JC}$	5.0				℃/W
工作结温和存储温度 Operating junction and storage temperature range	Tj, TSTG	-55---+150				℃

电特性 TA = 25℃ 除非另有规定。


Electrical Characteristics Ratings at 25℃ ambient temperature unless otherwise specified.

		符号 Symbols	SFAF502G	SFAF504G	SFAF506G	SFAF508G	单位 Unit
最大正向电压 Maximum forward voltage	I_F = 5.0A	V_F	0.975		1.30	1.70	V
最大反向电流 Maximum reverse current	TA= 25℃ TA=125℃	I_R	10 400				μA
最大反向恢复时间 MAX. Reverse Recovery Time	I_F=0.5A I_R=1.0A I_{REC}=0.25A	trr	35				nS

特性曲线 Characteristic Curves


正向特性曲线（典型值）

TYPICAL FORWARD CHARACTERISTIC



正向电流降额曲线

FORWARD CURRENT DERATING CURVE



浪涌特性曲线（最大值）

MAXIMUM NON REPETITIVE PEAK FORWARD SURGE CURRENT

