


5 JVR VARISTOR

Part Number	Maximum Allowable Voltage		Varistor Voltage V@0.1mA		Maximum Clamping Voltage V@ 5A	Withstanding Surge Current		Rated Wattage (W)	Energy 10/1000 s (J)	UL	CSA	VDE
	ACrms (V)	DC (V)	(V)	Tolerance Range		1Time (A)	2 Times (A)					
JVR05N180M65□△△	11	14	18	+ 20%	• 40	100	50	0.01	0.6	✓		
JVR05N220L 65□△△	14	18	22	+ 15%	• 48				0.7	✓		
JVR05N270K65□△△	17	22	27		• 60				0.9	✓		
JVR05N330K65□△△	20	26	33		• 73				1.1	✓		
JVR05N390K65□△△	25	31	39		• 86				1.2	✓		
JVR05N470K65□△△	30	38	47		• 104				1.5	✓		
JVR05N560K65□△△	35	45	56		• 123				1.8	✓		
JVR05N680K65□△△	40	56	68		• 150				2.1	✓		
JVR05N820K65□△△	50	65	82	+10%	145	400	200	0.1	2.8	✓		✓
JVR05N101K65□△△	60	85	100		175				3.5	✓		✓
JVR05N121K65□△△	75	100	120		210				4.0	✓		✓
JVR05N151K65□△△	95	125	150		260				5.5	✓		✓
JVR05N181K65□△△	115	150	180		320				6.5	✓		✓
JVR05N201K65□△△	130	170	200		355				7.1	✓	✓	✓
JVR05N221K65□△△	140	180	220		380				7.8	✓	✓	✓
JVR05N241K65□△△	150	200	240		415				8.4	✓	✓	✓
JVR05N271K65□△△	175	225	270		475				9.9	✓	✓	✓
JVR05N301K65□△△	195	250	300		525				10.5	✓	✓	✓
JVR05N331K65□△△	210	275	330		575				11.5	✓	✓	✓
JVR05N361K65□△△	230	300	360		620				13.0	✓	✓	✓
JVR05N391K65□△△	250	320	390		675				15.0	✓	✓	✓
JVR05N431K65□△△	275	350	430		745				16.5	✓	✓	✓
JVR05N471K65□△△	300	385	470		810				17.5	✓	✓	✓
JVR05N511K65□△△	320	418	510		880				18.5	✓	✓	
JVR05N561K65□△△	350	460	560		940				19.5	✓	✓	
JVR05N621K65□△△	385	505	620		1050				20.5	✓	✓	
JVR05N681K65□△△	420	560	680		1150				21.5	✓	✓	
JVR05N751K65□△△	460	615	750		1290				22.5	✓	✓	

1) The clamping voltage from 180M to 680K are tested with current 1A.
For application required ratings not shown, contact RFE application engineering.

- : Lead Style
Y: vertical kink (standard)
P: straight leads
△△ : Lead Length / Packing Method



PULSE RATING CURVES

