Customer Information Sheet

DRAWING No.: M50-311XX42	SHEET 2 OF 2	IF IN DOUBT - ASK	©	NOT TO SCALE	THIRD ANGLE PROJECTION	ALL DIMENSIONS IN mm









SPECIFICATIONS:
MATERIAL:
MOULDING = PA9T, UL94V-0, BLACK
CONTACT = PHOSPHOR BRONZE
FINISH:
CONTACT = NICKEL ALL OVER,
GOLD FLASH ON CONTACT AREA,
100% TIN ON TAILS
ELECTRICAL:
CURRENT RATING = 1A
VOLTAGE PROOF = 500V AC FOR ONE MINUTE
CONTACT RESISTANCE = 20mΩ MAX INITIAL,
30mΩ MAX AFTER CONDITIONING
INSULATION RESISTANCE = 1,000MΩ MIN
VOLTAGE PROOF = 500V AC/DC
MECHANICAL:
DURABILITY = 300 CYCLES MIN
INSERTION FORCE = 0.98N MAX PER CONTACT
WITHDRAWAL FORCE = 0.12N MIN PER CONTACT
ENVIRONMENTAL:
OPERATING TEMPERATURE = -40°C TO +105°C
PACKING:
TUBE
FOR COMPLETE SPECIFICATION, SEE COMPONENT
SPECIFICATION C029XX (LATEST ISSUE)

SB	9	31.05.16	13323
NAME	ISS.	DATE	C/NOTE
APPROVED:	S.BENNETT		
CHECKED:	M.PERREN		
DRAWN:	S.BENNETT		
CUSTOMER REF.:			
ASSEMBLY DRG:			

OBSOLETE

No. of contacts per row = 16 to 19, 21 to 24, 26 to 29, 31 to 50

Last Time Buy = 15th June 2018

ORDER CODE:

M50-311XX42

No. OF CONTACTS PER ROW:
03 to 15, 20, 25, 30

FINISH:
GOLD FLASH ON CONTACTS,
100 %TIN ON TAIL

NOTES:
1. ALL TOLERANCES ARE ±0.25 UNLESS OTHERWISE STATED.

HARWIN
www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.50mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL: SEE ABOVE
FINISH: SEE ABOVE
S/AREA: mm²

TITLE: 1.27mm PITCH DIL VERTICAL SMT SOCKET ASSY WITH POSTS

DRAWING NUMBER: M50-311XX42

SHT 2 OF 2