
LD1585C series


5A Low dropout fast response positive voltage regulator adjustable and fixed

Features

- Typical dropout 1.2V
- Fast transient response
- Three terminal adjustable or fixed output voltage 1.5V 1.8V, 2.5V, 2.85V, 3.3V, 5V, 8V, 9V
- Guaranteed output current up to 5A
- Output tolerance ±1% at 25°C and ±2% in full temperature range
- Internal power and thermal limit
- Wide operating temperature range 0°C to 125°C
- Package available: TO-220, D^2PAK/A
- Pinout compatibility with standard adjustable VREG



TO-220



D^2PAK/A

Description

The LD1585C is a LOW DROP Voltage Regulator able to provide up to 5A of Output Current. Dropout is guaranteed at a maximum of 1.4V at the maximum output current, decreasing at lower loads. The device has been improved to be utilized in low voltage applications where transient response and minimum input voltage are critical.

The most important feature of the device consist in lower dropout voltage and very fast transient response. A 2.85V output version is suitable for SCSI-2 active termination. Unlike PNP regulators, where a part of the output current is wasted as quiescent current, the LD1585C quiescent current flows into the load, so increase efficiency. Only a 10µF minimum capacitor is need for stability.

The device is supplied in TO-220, D^2PAK and D^2PAK/A. On chip trimming allows the regulator to reach a very tight output voltage tolerance, within ±1% at 25°C.

Order codes

Part number		
TO-220	**D^2PAK/A (T&R)**	**Output voltage**
	LD1585CD2M15R	1.5 V
	LD1585CD2M18R	1.8 V
	LD1585CD2M25R	2.5 V
	LD1585CD2M28R	2.85 V
	LD1585CD2M33R	3.3 V
LD1585CV50	LD1585CD2M50R	5.0 V
	LD1585CD2M80R	8.0 V
	LD1585CD2M90R	9.0 V
LD1585CV	LD1585CD2M-R	ADJ

Contents

1 Diagram 3

2 Pin configuration 4

3 Maximum ratings 5

4 Typical application 6

5 Electrical characteristics 7


6 Typical characteristics 16

7 Package mechanical data 20

8 Revision history 24


1 Diagram

Figure 1. Schematic diagram




2 Pin configuration

Figure 2. Pin connections (top view)



TO-220



D^2PAK/A

3 Maximum ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_I	DC Input Voltage	30	V
I_O	Output Current	Internally Limited	mA
P_D	Power Dissipation	Internally Limited	mW
T_{stg}	Storage Temperature Range	-55 to +150	°C
T_{op}	Operating Junction Temperature Range	0 to +125	°C


Note: Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these condition is not implied

Table 2. Thermal data

Symbol	Parameter	TO-220	D^2PAK/A	Unit
R_{thJC}	Thermal resistance junction-case	3	3	°C/W
R_{thJA}	Thermal resistance junction-ambient	50	62.5	°C/W

4 Typical application

Figure 3. Application circuits



$V_O = V_{REF}(1+R_2/R_1)$

5 Electrical characteristics

Table 3. Electrical characteristics of LD1585C#15 (V_I=4.5V, $C_I = C_O$ =10µF, T_J = 0 to 125°C, unless otherwise specified.)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_O	Output Voltage	I_O = 0 mA, T_J = 25°C	1.485	1.5	1.515	V
		I_O = 0 to 5A, V_I = 3 to 25V (1)	1.47	1.5	1.53	V
ΔV_O	Line Regulation	I_O = 0 mA, V_I = 3 to 15V T_J = 25°C		0.005	0.2	%
		I_O = 0 mA, V_I = 3 to 15V		0.005	0.2	%
ΔV_O	Load Regulation	I_O = 0 to 5A, T_J = 25°C		0.05	0.3	%
		I_O = 0 to 5A		0.05	0.5	%
V_d	Dropout Voltage	I_O = 5 A		1.2	1.4	V
I_q	Quiescent Current	$V_I \leq$25V		5	10	mA
I_{sc}	Short Circuit Current	$V_I - V_O$ = 5V	5.5	7		A
	Thermal Regulation	T_J = 25°C, 30ms pulse		0.004	0.02	%/W
SVR	Supply Voltage Rejection	f = 120 Hz, C_O = 25µF, I_O = 5A $V_I - V_O = 3 \pm 1$V	60	75		dB
eN	RMS Output Noise Voltage (% of V_O)	T_J = 25°C, f =10Hz to 10KHz		0.003		%
S	Temperature Stability			0.5		%
S	Long Term Stability	T_J = 125°C, 1000Hrs		0.03	1	%

1. See short-circuit current curve for available output current at fixed dropout.

Table 4. Electrical characteristics of LD1585C#18 (V_I=4.8V, $C_I = C_O$ =10µF, T_J = 0 to 125°C, unless otherwise specified.)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_O	Output Voltage	I_O = 0 mA, T_J = 25°C	1.782	1.8	1.818	V
		I_O = 0 to 5A, V_I = 3.3 to 25V (1)	1.764	1.8	1.836	V
ΔV_O	Line Regulation	I_O = 0 mA, V_I = 3.3 to 15V, T_J = 25°C		0.005	0.2	mV
		I_O = 0 mA, V_I = 3.3 to 15V		0.005	0.2	
ΔV_O	Load Regulation	I_O = 0 to 5A, T_J = 25°C		0.05	0.3	mV
		I_O = 0 to 5A		0.05	0.5	
V_d	Dropout Voltage	I_O = 5 A		1.2	1.4	V
I_q	Quiescent Current	$V_I \leq$25V		5	10	mA
I_{sc}	Short Circuit Current	$V_I - V_O$ = 5.5V	5.5	7		A
	Thermal Regulation	T_J = 25°C, 30ms pulse		0.004	0.02	%/W
SVR	Supply Voltage Rejection	f = 120 Hz, C_O = 25µF, I_O = 5A $V_I - V_O = 3 \pm 1$V	60	75		dB
eN	RMS Output Noise Voltage (% of V_O)	T_J = 25°C, f =10Hz to 10KHz		0.003		%
S	Temperature Stability			0.5		%
S	Long Term Stability	T_J = 125°C, 1000Hrs		0.03	1	%

1. See short-circuit current curve for available output current at fixed dropout.

Table 5. Electrical characteristics of LD1585C#25 (V_I=5.5V, $C_I = C_O$ =10µF, T_J = 0 to 125°C, unless otherwise specified.)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_O	Output Voltage	I_O = 0 mA, T_J = 25°C	2.475	2.5	2.525	V
		I_O = 0 to 5A, V_I = 4 to 25V (1)	2.45	2.5	2.55	V
ΔV_O	Line Regulation	I_O = 0 mA, V_I = 4 to 15V, T_J = 25°C		0.005	0.2	mV
		I_O = 0 mA, V_I = 4 to 15V		0.005	0.2	
ΔV_O	Load Regulation	I_O = 0 to 5A, T_J = 25°C		0.05	0.3	mV
		I_O = 0 to 5A		0.05	0.5	
V_d	Dropout Voltage	I_O = 5 A		1.2	1.4	V
I_q	Quiescent Current	$V_I \leq$25V		5	10	mA
I_{sc}	Short Circuit Current	$V_I - V_O$ = 5.5V	5.5	7		A
	Thermal Regulation	T_J = 25°C, 30ms pulse		0.004	0.02	%/W
SVR	Supply Voltage Rejection	f = 120 Hz, C_O = 25µF, I_O = 5A $V_I - V_O = 3 \pm 1$V	60	75		dB
eN	RMS Output Noise Voltage (% of V_O)	T_J = 25°C, f =10Hz to 10KHz		0.003		%
S	Temperature Stability			0.5		%
S	Long Term Stability	T_J = 125°C, 1000Hrs		0.03	1	%

1. See short-circuit current curve for available output current at fixed dropout.

Table 6. Electrical characteristics of LD1585C#285 (V_I=5.85V, C_I = C_O =10µF, T_J = 0 to 125°C, unless otherwise specified.)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_O	Output Voltage	I_O = 0 mA, T_J = 25°C	2.821	2.85	2.879	V
		I_O = 0 to 5A, V_I = 4.5 to 25V (1)	2.793	2.85	2.907	V
ΔV_O	Line Regulation	I_O = 0 mA, V_I = 4.5 to 15V, T_J = 25°C		0.005	0.2	mV
		I_O = 0 mA, V_I = 4.5 to 15V		0.005	0.2	
ΔV_O	Load Regulation	I_O = 0 to 5A, T_J = 25°C		0.05	0.3	mV
		I_O = 0 to 5A		0.05	0.5	
V_d	Dropout Voltage	I_O = 5 A		1.2	1.4	V
I_q	Quiescent Current	$V_I \leq$25V		5	10	mA
I_{sc}	Short Circuit Current	V_I - V_O = 5.5V	5.5	7		A
	Thermal Regulation	T_J = 25°C, 30ms pulse		0.004	0.02	%/W
SVR	Supply Voltage Rejection	f = 120 Hz, C_O = 25µF, I_O = 5A V_I - V_O = 3 ± 1V	60	75		dB
eN	RMS Output Noise Voltage (% of V_O)	T_J = 25°C, f =10Hz to 10KHz		0.003		%
S	Temperature Stability			0.5		%
S	Long Term Stability	T_J = 125°C, 1000Hrs		0.03	1	%

1. See short-circuit current curve for available output current at fixed dropout.

Table 7. Electrical characteristics of LD1585C#33 (V_I=6.3V, $C_I = C_O$ =10µF, T_J = 0 to 125°C, unless otherwise specified.)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_O	Output Voltage	I_O = 0 mA, T_J = 25°C	3.267	3.3	3.333	V
		I_O = 0 to 5A, V_I = 4.8 to 25V (1)	3.234	3.35	3.366	V
ΔV_O	Line Regulation	I_O = 0 mA, V_I = 4.8 to 15V, T_J = 25°C		0.005	0.2	mV
		I_O = 0 mA, V_I = 4.9 to 15V		0.005	0.2	
ΔV_O	Load Regulation	I_O = 0 to 5A, T_J = 25°C		0.05	0.3	mV
		I_O = 0 to 5A		0.05	0.5	
V_d	Dropout Voltage	I_O = 5 A		1.2	1.4	V
I_q	Quiescent Current	$V_I \leq$25V		5	10	mA
I_{sc}	Short Circuit Current	$V_I - V_O$ = 5.5V	5.5	7		A
	Thermal Regulation	T_J = 25°C, 30ms pulse		0.004	0.02	%/W
SVR	Supply Voltage Rejection	f = 120 Hz, C_O = 25µF, I_O = 5A $V_I - V_O = 3 \pm 1$V	60	75		dB
eN	RMS Output Noise Voltage (% of V_O)	T_J = 25°C, f =10Hz to 10KHz		0.003		%
S	Temperature Stability			0.5		%
S	Long Term Stability	T_J = 125°C, 1000Hrs		0.03	1	%

1. See short-circuit current curve for available output current at fixed dropout.

Table 8. Electrical characteristics of LD1585C#50 (V_I=8V, C_I = C_O =10µF, T_J = 0 to 125°C, unless otherwise specified.)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_O	Output Voltage	I_O = 0 mA, T_J = 25°C	4.95	5	5.05	V
		I_O = 0 to 5A, V_I = 6.5 to 30V (1)	4.9	5	5.1	V
ΔV_O	Line Regulation	I_O = 0 mA, V_I = 6.5 to 20V, T_J = 25°C		0.005	0.2	mV
		I_O = 0 mA, V_I = 6.5 to 20V		0.005	0.2	
ΔV_O	Load Regulation	I_O = 0 to 5A, T_J = 25°C		0.05	0.3	mV
		I_O = 0 to 5A		0.05	0.5	
V_d	Dropout Voltage	I_O = 5 A		1.2	1.4	V
I_q	Quiescent Current	$V_I \leq$25V		5	10	mA
I_{sc}	Short Circuit Current	V_I - V_O = 5.5V	5.5	7		A
	Thermal Regulation	T_J = 25°C, 30ms pulse		0.004	0.02	%/W
SVR	Supply Voltage Rejection	f = 120 Hz, C_O = 25µF, I_O = 5A V_I - V_O = 3 ± 1V	60	75		dB
eN	RMS Output Noise Voltage (% of V_O)	T_J = 25°C, f =10Hz to 10KHz		0.003		%
S	Temperature Stability			0.5		%
S	Long Term Stability	T_J = 125°C, 1000Hrs		0.03	1	%

1. See short-circuit current curve for available output current at fixed dropout.

Table 9. Electrical characteristics of LD1585C#80 (V_I=11V, $C_I = C_O$ =10µF, T_J = 0 to 125°C, unless otherwise specified.)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_O	Output Voltage	I_O = 0 mA, T_J = 25°C	7.92	8	8.08	V
		I_O = 0 to 5A, V_I = 9.5 to 30V (1)	7.84	8	8.16	V
ΔV_O	Line Regulation	I_O = 0 mA, V_I = 9.5 to 20V, T_J = 25°C		0.005	0.2	mV
		I_O = 0 mA, V_I = 9.5 to 20V		0.005	0.2	
ΔV_O	Load Regulation	I_O = 0 to 5A, T_J = 25°C		0.05	0.3	mV
		I_O = 0 to 5A		0.05	0.5	
V_d	Dropout Voltage	I_O = 5 A		1.2	1.4	V
I_q	Quiescent Current	$V_I \leq$25V		5	10	mA
I_{sc}	Short Circuit Current	$V_I - V_O$ = 5.5V	5.5	7		A
	Thermal Regulation	T_J = 25°C, 30ms pulse		0.004	0.02	%/W
SVR	Supply Voltage Rejection	f = 120 Hz, C_O = 25µF, I_O = 5A $V_I - V_O = 3 \pm 1$V	60	75		dB
eN	RMS Output Noise Voltage (% of V_O)	T_J = 25°C, f =10Hz to 10KHz		0.003		%
S	Temperature Stability			0.5		%
S	Long Term Stability	T_J = 125°C, 1000Hrs		0.03	1	%

1. See short-circuit current curve for available output current at fixed dropout.

Table 10. Electrical characteristics of LD1585C#90 (V_I=12V, $C_I = C_O$ =10µF, T_J = 0 to 125°C, unless otherwise specified.)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_O	Output Voltage	I_O = 0 mA, T_J = 25°C	8.91	9	9.09	V
		I_O = 0 to 5A, V_I = 10.5 to 30V (1)	8.82	9	9.18	V
ΔV_O	Line Regulation	I_O = 0 mA, V_I = 10.5 to 20V, T_J = 25°C		0.005	0.2	mV
		I_O = 0 mA, V_I = 10.5 to 20V		0.005	0.2	
ΔV_O	Load Regulation	I_O = 0 to 5A, T_J = 25°C		0.05	0.3	mV
		I_O = 0 to 5A		0.05	0.5	
V_d	Dropout Voltage	I_O = 5 A		1.2	1.4	V
I_q	Quiescent Current	$V_I \leq$25V		5	10	mA
I_{sc}	Short Circuit Current	$V_I - V_O$ = 5.5V	5.5	7		A
	Thermal Regulation	T_J = 25°C, 30ms pulse		0.004	0.02	%/W
SVR	Supply Voltage Rejection	f = 120 Hz, C_O = 25µF, I_O = 5A $V_I - V_O = 3 \pm 1$V	60	75		dB
eN	RMS Output Noise Voltage (% of V_O)	T_J = 25°C, f =10Hz to 10KHz		0.003		%
S	Temperature Stability			0.5		%
S	Long Term Stability	T_J = 125°C, 1000Hrs		0.03	1	%

1. See short-circuit current curve for available output current at fixed dropout.

Table 11. Electrical characteristics of LD1585C# (V_I=4.25V, C_I = C_O =10µF, T_J = 0 to 125°C, unless otherwise specified.)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_O	Output Voltage	I_O = 10mA, V_I - V_O = 3V, T_J = 25°C	1.237	1.25	1.263	V
		I_O = 10mA to 5A, V_I - V_O =1.5 to 25V (1)	1.225	1.25	1.275	V
ΔV_O	Line Regulation	I_O = 10mA, V_I = 2.75 to 15V T_J = 25°C		0.015	0.2	%
		I_O = 10mA, V_I = 2.75 to 15V		0.1	0.2	%
ΔV_O	Load Regulation	I_O = 10mA to 5A, T_J = 25°C		0.1	0.3	%
		I_O = 0 to 5A		0.25	0.5	%
V_d	Dropout Voltage	I_O = 5A		1.2	1.4	V
$I_{O(min)}$	Minimum Load Current	V_I = 25V		3	10	mA
I_{sc}	Short Circuit Current	V_I - V_O = 5.5V	5.5	7		A
	Thermal Regulation	T_J = 25°C, 30ms pulse		0.004	0.02	%/W
SVR	Supply Voltage Rejection	f = 120 Hz, C_O = 25µF, C_{ADJ} = 25µF, I_O = 5A, V_I - V_O = 3 ± 1V	60	75		dB
I_{ADJ}	Adjust Pin Current	I_O = 10 mA		50	100	µA
ΔI_{ADJ}	Adjust Pin Current Change	I_O = 10mA to 5A, V_I = 3 to 25V (1)		0.2	5	µA
eN	RMS Output Noise Voltage (% of V_O)	T_J = 25°C, f =10Hz to 10KHz		0.003		%
S	Temperature Stability			0.5		%
S	Long Term Stability	T_J = 125°C, 1000Hrs		0.5		%

1. See short-circuit current curve for available output current at fixed dropout.

6 Typical characteristics

(unless otherwise specified T_J=25°C, C_I=C_O=10µF tant.)

Figure 4. Output voltage vs temperature




Figure 5. Short circuit current vs dropout voltage




Figure 6. Line regulation vs temperature




Figure 7. Line regulation vs temperature




Figure 8. Load regulation vs temperature




Figure 9. Load regulation vs temperature




Figure 10. Dropout voltage vs temperature




Figure 11. Dropout voltage vs output current




Figure 12. Adjust pin current vs input voltage




Figure 13. Adjust pin current vs temperature




Figure 14. Adjust pin current change vs temperature




Figure 15. Quiescent current vs temperature




Figure 16. Reference voltage vs temperature




Figure 17. Minimum load current vs temperature




Figure 18. Supply voltage rejection vs output current




Figure 19. Supply voltage rejection vs output current




Figure 20. Supply voltage rejection vs frequency




Figure 21. Supply voltage rejection vs frequency




Figure 22. Supply voltage rejection vs temperature




Figure 23. Supply voltage rejection vs temperature






Figure 24. Line transient




V_I=15 to 16V, I_O=200mA, C_I = 1µF(tant), C_O=10µF(tant)

Figure 25. Load transient



V_I=15 V, I_O=0.1 to 5 A, C_I = 10µF(tant), C_O=10µF(tant)

Figure 26. Load transient




V_I=7 V, I_O=0.1 to 5 A, C_I = 10µF(tant), C_O=10µF(tant)

7 Package mechanical data

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a Lead-free second level interconnect. The category of second Level Interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com.

D^2PAK/A MECHANICAL DATA


DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A	4.40		4.60	0.173		0.181
A1	2.49		2.69	0.098		0.106
A2	0.03		0.23	0.001		0.009
B	0.7		0.93	0.028		0.037
B1	0.8		1.3	0.031		0.051
B2	1.14		1.7	0.045		0.067
C	0.45		0.60	0.018		0.024
C2	1.23		1.36	0.048		0.054
D	8.95		9.35	0.352		0.368
D1		8			0.315	
E	10		10.4	0.394		0.409
E1		8.5			0.335	
G	4.88		5.28	0.192		0.208
L	15		15.85	0.591		0.624
L2	1.27		1.4	0.050		0.055
M	2.4		3.2	0.094		0.126
R		0.4			0.016	
V2	0°		8°	0°		8°



7106164/D

TO-220 MECHANICAL DATA


DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A	4.40		4.60	0.173		0.181
C	1.23		1.32	0.048		0.051
D	2.40		2.72	0.094		0.107
D1		1.27			0.050	
E	0.49		0.70	0.019		0.027
F	0.61		0.88	0.024		0.034
F1	1.14		1.70	0.044		0.067
F2	1.14		1.70	0.044		0.067
G	4.95		5.15	0.194		0.203
G1	2.4		2.7	0.094		0.106
H2	10.0		10.40	0.393		0.409
L2		16.4			0.645	
L4	13.0		14.0	0.511		0.551
L5	2.65		2.95	0.104		0.116
L6	15.25		15.75	0.600		0.620
L7	6.2		6.6	0.244		0.260
L9	3.5		3.93	0.137		0.154
DIA.	3.75		3.85	0.147		0.151



P011C

Tape & Reel D^2PAK-P^2PAK-D^2PAK/A-P^2PAK/A MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			180			7.086
C	12.8	13.0	13.2	0.504	0.512	0.519
D	20.2			0.795		
N	60			2.362		
T			14.4			0.567
Ao	10.50	10.6	10.70	0.413	0.417	0.421
Bo	15.70	15.80	15.90	0.618	0.622	0.626
Ko	4.80	4.90	5.00	0.189	0.193	0.197
Po	3.9	4.0	4.1	0.153	0.157	0.161
P	11.9	12.0	12.1	0.468	0.472	0.476



8 Revision history

Table 12. Revision history

Date	Revision	Changes
07-Oct-2004	3	Mistake order codes - Table 1.
20-Oct-2005	4	Order codes has been updated.
08-Jun-2007	5	Order codes has been updated and the document has been reformatted.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST’s terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST’S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER’S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com