


SECT B-B







P/N	R/C
U261-24XXN-4B0136	
U261-24XXN-4B0135	R2(5.1KΩ)
U261-24XXN-4B0151	R1(56KΩ)

U261-24XXN-4B0136



C TYPE PLUG:

PCB:




REMARKS:

- CONTACT INSERTION AND WITHDRAW FORCE :
 - Insertion force : 5N-20N max.
 - Withdrawal force : 8N-20N.
 - Durability : 10000Cycles.
- ELECTRIC PROPERTY :
 - Contact current rating : 3A.
 - Dielectric Strength : 100V AC(RMS).
 - Insulation Resistance : 100 megaohms min.
 - Contact resistance : 40mOhms MAX.FOR VBUS,GND AND OTHER CONTACT 50mOhms MAX.AFTER ENVIRONMENT TEST
- AMBIENT TEMPERATURE :
 - Operating temperature : -55°C to +85°C.



D
2:1



SECT A-A

A12	A11	A10	A9	A8	A7	A6	A5	A4	A3	A2	A1
GND	RX2+	RX2-	Vbus	SBU1	D-	D+	CC	Vbus	TX1-	TX1+	GND
GND	TX2+	TX2-	Vbus	Vconn			SBU2	Vbus	RX1-	RX1+	GND
B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12

6	Shrapnel	SUS T=0.10mm	
5	Shell	SUS T=0.15mm	Ovep-plating: Ni
4	Terminal	C7025 T=0.15mm	Ovep-plating: Au Ni/Sn
3	Latch	SUS T=0.4mm	
2	Housing	LCP	UL94-0
1	Housing Stopper	LCP	UL94-0
ITEM	DESCRIPTION	MATERIAL	REMARKS

REVISIONS					UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: 3.1 TYPE C	
Δx					ANGLAR			VIEW:	PART NO.:	
Δx					L ≤ 4			UNIT: mm/in	DWG NO.:	
Δx					4 < L ≤ 16			SIZE: A4	U261-24XXN-4B0136	
MARK	DESCRIPTION	DATE	REVISED	APPROVED	16 < L ≤ 63				WEIGHT	
					L > 63				SHEET	
									REVISION	
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn					KXB INDUSTRIAL PRECISION CO.,LIMITED			1.0g	1/1	A0