# Printed-circuit board connector - BCVP-381WF- 9 GN - 5450049

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



The figure shows a 5-pos. version of the product in gray

Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 9, Pitch: 3.81 mm, Connection method: Screw connection with tension sleeve, Color: pastel green, Contact surface: Tin




## Key Commercial Data

| | |
|---|---|
| Packing unit | 1 pc |
| Minimum order quantity | 100 pc |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

## Technical data

### Dimensions

| | |
|---|---|
| Height | 12.5 mm |
| Pitch | 3.81 mm |
| Dimension a | 30.48 mm |

### General

| | |
|---|---|
| Range of articles | BCVP-WF |
| Insulating material group | I |
| Rated surge voltage (III/3) | 2.5 kV |
| Rated surge voltage (III/2) | 2.5 kV |
| Rated surge voltage (II/2) | 2.5 kV |
| Rated voltage (III/2) | 160 V |
| Rated voltage (II/2) | 320 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current $I_N$ | 8 A |

# Printed-circuit board connector - BCVP-381WF- 9 GN - 5450049

## Technical data

### General

| | |
|---|---|
| Nominal cross section | 1.5 mm² |
| Maximum load current | 8 A (with 1.5 mm² conductor cross section) |
| Insulating material | PA |
| Flammability rating according to UL 94 | V0 |
| Number of positions | 9 |

### Connection data

| | |
|---|---|
| Conductor cross section solid min. | 0.2 mm² |
| Conductor cross section solid max. | 1.5 mm² |
| Conductor cross section flexible min. | 0.2 mm² |
| Conductor cross section flexible max. | 1.5 mm² |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.25 mm² |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 1.5 mm² |
| Conductor cross section flexible, with ferrule with plastic sleeve min. | 0.25 mm² |
| Conductor cross section flexible, with ferrule with plastic sleeve max. | 0.5 mm² |
| Conductor cross section AWG min. | 24 |
| Conductor cross section AWG max. | 16 |
| 2 conductors with same cross section, solid min. | 0.2 mm² |
| 2 conductors with same cross section, solid max. | 0.5 mm² |
| 2 conductors with same cross section, stranded min. | 0.2 mm² |
| 2 conductors with same cross section, stranded max. | 0.75 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. | 0.25 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. | 0.34 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm² |

### Standards and Regulations

| | |
|---|---|
| Connection in acc. with standard | EN-VDE |
| | CUL |
| Flammability rating according to UL 94 | V0 |

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |

# Printed-circuit board connector - BCVP-381WF- 9 GN - 5450049

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27261101 |
| eCl@ss 7.0 | 27440401 |
| eCl@ss 8.0 | 27440309 |
| eCl@ss 9.0 | 27440309 |

### ETIM

| | |
|---|---|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002638 |

### UNSPSC

| | |
|---|---|
| UNSPSC 6.01 | 30211801 |
| UNSPSC 7.0901 | 39121432 |
| UNSPSC 11 | 39121432 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121432 |

## Approvals

### Approvals

Approvals

UL Recognized / cUL Recognized / VDE Gutachten mit Fertigungsüberwachung / IECEE CB Scheme / cULus Recognized

Ex Approvals

Approvals submitted

### Approval details

# Printed-circuit board connector - BCVP-381WF- 9 GN - 5450049

## Approvals

UL Recognized

| | B | D |
|---|---|---|
| mm²/AWG/kcmil | 30-14 | 30-14 |
| Nominal current IN | 8 A | 8 A |
| Nominal voltage UN | 300 V | 300 V |

cUL Recognized

| | B | D |
|---|---|---|
| mm²/AWG/kcmil | 30-14 | 30-14 |
| Nominal current IN | 8 A | 8 A |
| Nominal voltage UN | 300 V | 300 V |


VDE Gutachten mit Fertigungsüberwachung

IECEE CB Scheme

cULus Recognized

## Drawings

Diagram



Phoenix Contact 2016 © - all rights reserved
http://www.phoenixcontact.com