





LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			B	REVISED PER ECO-08-031349	16DEC08	HMR	MW



- NOTES:
1. ALL COLORS AND MATERIALS MADE FROM ONE TOOL.
 2. SOME DIMENSIONS MAY VARY DUE TO DIFFERENT COMPOUND SHRINKAGE FACTOR.
 - 3.
 4. MINOR FLASH ACCEPTABLE ON INSERT THREAD.
 5. BLACK FINISH/NICKEL PLATING ON INSIDE THREADS REMOVED DUE TO MOLDING PROCESS PERMITTED.
 6. RUBBER TO METAL BOND MUST MEET OR EXCEED THE TEAR STRENGTH OF RUBBER.
 7. RUBBER OVERLAY PERMISSIBLE OVER HEX FLATS AS SHOWN IN THE DRAWING.
 - 8.
 9. TREAT WITH PERMANENT LUBRICANT
 10. COMPONENTS MUST COMPLY WITH THE EUROPEAN DIRECTIVE 2002/95/EC ON RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT (ROHS DIRECTIVE).

SECTION A-A

ALCO PART NUMBER	PART NUMBER	HEX NUT MATERIAL	RUBBER BOOT MATERIAL
BT1532004	1825600-1	BRASS, BLACK OXIDE PER MIL-F-495	SILICONE, COLOR BLACK
BT1532204	1825600-2	BRASS, NICKEL PLATE PER QQ-N-290	SILICONE, COLOR RED
BT1532804	1825600-3	BRASS, NICKEL PLATE PER QQ-N-290	SILICONE, COLOR GRAY

NO.	DESCRIPTION	DRAWING NO.	MATERIAL			
①	NUT 15/32-32 UNS-2B	HEX NUT 15/32-32	BRASS, FINISH AS PER ABOVE TABLE			
②	RUBBER BOOT	RUBBER BOOT	SILICONE PER ZZ-R-765, CLASS 3A, GRADE 50 COLOR AS PER ABOVE TABLE			
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R BROWN 03JAN2008	Tyco Electronics Corporation Harrisburg, PA 17105-3608			
		CHK M WILBOURN 03JAN2008				
DIMENSIONS: INCHES		APVD M WILBOURN 03JAN2008	NAME 15/32-32 TOGGLE SWITCH BOOT SEAL			
		PRODUCT SPEC				
		APPLICATION SPEC				
		—				
MATERIAL —		WEIGHT —	SIZE A2	CAGE CODE 00779	DRAWING NO C=1825600	RESTRICTED TO —
		FINISH —	CUSTOMER DRAWING		SCALE 3:1	SHEET 1 of 1
					REV B	