COMPLEMENTARY N AND P-CHANNEL ENHANCEMENT-MODE POWER MOSFETS

Simple drive requirement

Low on-resistance

Fast switching performance



SO-8

N-Ch	BV_{DSS}	60V
	$R_{DS(ON)}$	36mΩ
	I_D	6A
P-Ch	BV_{DSS}	-60V
	$R_{DS(ON)}$	72mΩ
	I_D	-4.2A

Description

Power MOSFETs from Silicon Standard provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The SO-8 package is widely preferred for commercial and industrial surface mount applications and is well suited for low-voltage applications such as DC/DC converters.



Absolute Maximum Ratings

Symbol	Parameter	Rating		Units
		N-channel	P-channel	
V_{DS}	Drain-Source Voltage	60	-60	V
V_{GS}	Gate-Source Voltage	±20	±20	V
I_D @ T_A=25°C	Continuous Drain Current[3]	6	-4.2	A
I_D @ T_A=70°C	Continuous Drain Current[3]	4.7	-3.3	A
I_{DM}	Pulsed Drain Current[1]	30	-30	A
P_D @ T_A=25°C	Total Power Dissipation	2.0		W
	Linear Derating Factor	0.016		W/°C
T_{STG}	Storage Temperature Range	-55 to 150		°C
T_J	Operating Junction Temperature Range	-55 to 150		°C

Thermal Data

Symbol	Parameter		Value	Unit
Rthj-a	Thermal Resistance Junction-ambient[3]	Max.	62.5	°C/W

N-channel Electrical Characteristics @ T_j=25°C(unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D=250uA	60	-	-	V
$\Delta BV_{DSS}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to 25°C,I_D=1mA	-	0.04	-	V/°C
$R_{DS(ON)}$	Static Drain-Source On-Resistance[2]	V_{GS}=10V, I_D=5A	-	-	36	mΩ
		V_{GS}=4.5V, I_D=3A	-	-	42	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=250uA	1	-	3	V
g_{fs}	Forward Transconductance	V_{DS}=10V, I_D=5A	-	8	-	S
I_{DSS}	Drain-Source Leakage Current (T_j=25°C)	V_{DS}=60V, V_{GS}=0V	-	-	1	uA
	Drain-Source Leakage Current (T_j=70°C)	V_{DS}=48V, V_{GS}=0V	-	-	25	uA
I_{GSS}	Gate-Source Leakage	V_{GS}=±20V	-	-	±100	nA
Q_g	Total Gate Charge[2]	I_D=5A	-	18	29	nC
Q_{gs}	Gate-Source Charge	V_{DS}=48V	-	5	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	V_{GS}=4.5V	-	10	-	nC
$t_{d(on)}$	Turn-on Delay Time[2]	V_{DS}=30V	-	10	-	ns
t_r	Rise Time	I_D=1A	-	6	-	ns
$t_{d(off)}$	Turn-off Delay Time	R_G=3.3Ω,V_{GS}=10V	-	32	-	ns
t_f	Fall Time	R_D=30Ω	-	10	-	ns
C_{iss}	Input Capacitance	V_{GS}=0V	-	1670	2670	pF
C_{oss}	Output Capacitance	V_{DS}=25V	-	160	-	pF
C_{rss}	Reverse Transfer Capacitance	f=1.0MHz	-	117	-	pF

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_{SD}	Forward On Voltage[2]	I_S=1.7A, V_{GS}=0V	-	-	1.2	V
t_{rr}	Reverse Recovery Time[2]	I_S=5A, V_{GS}=0V	-	34	-	ns
Q_{rr}	Reverse Recovery Charge	dI/dt=100A/μs	-	48	-	nC

P-channel Electrical Characteristics @ T_j=25°C(unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D=-250uA	-60	-	-	V
$\Delta BV_{DSS}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to 25°C,I_D=-1mA	-	-0.04	-	V/°C
$R_{DS(ON)}$	Static Drain-Source On-Resistance[2]	V_{GS}=-10V, I_D=-4A	-	-	72	mΩ
		V_{GS}=-4.5V, I_D=-3A	-	-	88	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=-250uA	-1	-	-3	V
g_{fs}	Forward Transconductance	V_{DS}=-10V, I_D=-4A	-	6	-	S
I_{DSS}	Drain-Source Leakage Current (Tj=25°C)	V_{DS}=-60V, V_{GS}=0V	-	-	-1	uA
	Drain-Source Leakage Current (Tj=70°C)	V_{DS}=-48V, V_{GS}=0V	-	-	-25	uA
I_{GSS}	Gate-Source Leakage	V_{GS}=±20V	-	-	±100	nA
Q_g	Total Gate Charge[2]	I_D=-4A	-	21	34	nC
Q_{gs}	Gate-Source Charge	V_{DS}=-48V	-	5	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	V_{GS}=-4.5V	-	9	-	nC
$t_{d(on)}$	Turn-on Delay Time[2]	V_{DS}=-30V	-	12	-	ns
t_r	Rise Time	I_D=-1A	-	6	-	ns
$t_{d(off)}$	Turn-off Delay Time	R_G=3.3Ω ,V_{GS}=-10V	-	82	-	ns
t_f	Fall Time	R_D=30Ω	-	36	-	ns
C_{iss}	Input Capacitance	V_{GS}=0V	-	1780	2850	pF
C_{oss}	Output Capacitance	V_{DS}=-25V	-	157	-	pF
C_{rss}	Reverse Transfer Capacitance	f=1.0MHz	-	130	-	pF

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_{SD}	Forward On Voltage[2]	I_S=-1.7A, V_{GS}=0V	-	-	-1.2	V
t_{rr}	Reverse Recovery Time[2]	I_S=-4A, V_{GS}=0V	-	43	-	ns
Q_{rr}	Reverse Recovery Charge	dI/dt=-100A/μs	-	87	-	nC

Notes:

1.Pulse width limited by max. junction temperature.

2.Pulse width ≤300us , duty cycle ≤2%.

3.Surface mounted on 1 in^2 copper pad of FR4 board ; 135°C/W when mounted on min. copper pad.

N-channel



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. On-Resistance vs. Gate Voltage



Fig 4. Normalized On-Resistance v.s. Junction Temperature



Fig 5. Forward Characteristic of Reverse Diode



Fig 6. Gate Threshold Voltage vs. Junction Temperature

N-channel



Fig 7. Gate Charge Characteristics



Fig 8. Typical Capacitance Characteristics



Fig 9. Maximum Safe Operating Area



Fig 10. Effective Transient Thermal Impedance



Fig 11. Switching Time Waveform



Fig 12. Gate Charge Waveform

P-channel



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. On-Resistance vs. Gate Voltage



Fig 4. Normalized On-Resistance vs. Junction Temperature



Fig 5. Forward Characteristic of Reverse Diode



Fig 6. Gate Threshold Voltage vs. Junction Temperature

P-channel



Fig 7. Gate Charge Characteristics



Fig 8. Typical Capacitance Characteristics



Fig 9. Maximum Safe Operating Area



Fig 10. Effective Transient Thermal Impedance



Fig 11. Switching Time Waveform



Fig 12. Gate Charge Waveform

Information furnished by Silicon Standard Corporation is believed to be accurate and reliable. However, Silicon Standard Corporation makes no guarantee or warranty, express or implied, as to the reliability, accuracy, timeliness or completeness of such information and assumes no responsibility for its use, or for infringement of any patent or other intellectual property rights of third parties that may result from its use. Silicon Standard reserves the right to make changes as it deems necessary to any products described herein for any reason, including without limitation enhancement in reliability, functionality or design. No license is granted, whether expressly or by implication, in relation to the use of any products described herein or to the use of any information provided herein, under any patent or other intellectual property rights of Silicon Standard Corporation or any third parties.