ADELS contact

PCB Connectors

GSK 801/ 5

Terminal Block Vertical, Pin Spacing: 5.0 mm, 5 pole, Insulating Material: PA 6.6, Voltage Rating: 300 V, Current Rating: 24 A



Order Info

Reference Number (ref. no.)	321605
Applications	Lighting, Electrical Appliances, Transformers, Electronics
PU	500
EAN	4028012109166

Type

Type	Terminal Block Vertical
Number of poles	5 pole
Clamping Units per Pole	1
Colour	white
Connection Type	Screw

Technical Data

Voltage Rating	300 V
Current Rating	24 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	0.5 mm²
Core Cross-Section max.	6.0 mm²
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	6.7-7.0 mm
Assembly Contact Screw	0.6x3.5 / ↻ 0.5 Nm
Pin Spacing	5.0 mm
Approbation UL	GSK801_19850129_19941222_UL_E63492_1-03_Description_web.p
Approbation CSA	GSK_GST_Printklemmen_Serie_20160404_CSA_70070893_Certificat