


# SI2302

N-Channel 20-V(D-S) MOSFET

<b>V<sub>(BR)DSS</sub></b>	<b>R<sub>D(on)MAX</sub></b>	<b>I<sub>D</sub></b>
20V	0.050Ω@ 4.5V	3A
	0.065Ω@ 2.5V	



## General FEATURE

- TrenchFET Power MOSFET
- Lead free product is acquired
- Surface mount package

## APPLICATION

- Load Switch for Portable Devices
- DC/DC Converter

## Maximum ratings ( $T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V <sub>DS</sub>	20	V
Gate-Source Voltage	V <sub>GS</sub>	±10	
Continuous Drain Current	I <sub>D</sub>	3.0	A
Pulsed Drain Current*1	I <sub>DM</sub>	10	
Continuous Source-Drain Diode Current	I <sub>S</sub>	1.0	
Maximum Power Dissipation	P <sub>D</sub>	1.0	W
Thermal Resistance from Junction to Ambient( $t \leq 5\text{s}$ )	R <sub>θJA</sub>	156	°C/W
Junction Temperature	T <sub>J</sub>	150	°C
Storage Temperature	T <sub>stg</sub>	-55 ~+150	

Note :

\*1. Pulse Width  $\leq 300\mu\text{s}$ , Duty cycle  $\leq 2\%$

**MOSFET ELECTRICAL CHARACTERISTICS**
**T<sub>a</sub> =25 °C unless otherwise specified**

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
<b>Static</b>						
Drain-source breakdown voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = -250μA	20			V
Gate-source threshold voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -250μA	0.5	0.8	1.0	
Gate-source leakage	I <sub>GSS</sub>	V <sub>DS</sub> = 0V, V <sub>GS</sub> = ±10V			±100	nA
Zero gate voltage drain current	I <sub>DSS</sub>	V <sub>DS</sub> = 16V, V <sub>GS</sub> = 0V			1	μA
Drain-source on-state resistance <sup>a</sup>	R <sub>DSS(on)</sub>	V <sub>GS</sub> = 4.5V, I <sub>D</sub> = 3A		0.045	0.050	Ω
		V <sub>GS</sub> = 2.5V, I <sub>D</sub> = 2A		0.055	0.065	
Forward transconductance <sup>a</sup>	g <sub>fs</sub>	V <sub>DS</sub> = 5V, I <sub>D</sub> = 3A		8.0	-	S
<b>Dynamic<sup>b</sup></b>						
Input capacitance	C <sub>iss</sub>	V <sub>DS</sub> = 10V, V <sub>GS</sub> = 0V, f = 1MHz		300		pF
Output capacitance	C <sub>oss</sub>			120		
Reverse transfer capacitance	C <sub>rss</sub>			80		
Total gate charge	Q <sub>g</sub>	V <sub>DS</sub> = 10V, V <sub>GS</sub> = 4.5V, I <sub>D</sub> = 3A		4.0		nC
Gate-source charge	Q <sub>gs</sub>			0.65		
Gate-drain charge	Q <sub>gd</sub>			1.6		
Turn-on delay time	t <sub>d(on)</sub>	V <sub>DD</sub> = 10V, I <sub>D</sub> = 3A V <sub>GEN</sub> = 4.5V, R <sub>g</sub> = 6Ω		15.0		ns
Rise time	t <sub>r</sub>			85.0		
Turn-off delay time	t <sub>d(off)</sub>			45.0		
Fall time	t <sub>f</sub>			20.0		
<b>Drain-source body diode characteristics</b>						
Continuous source-drain diode current	I <sub>s</sub>	T <sub>c</sub> = 25°C			1.0	A
Body diode voltage	V <sub>SD</sub>	I <sub>s</sub> = 1.0A		0.7	1.3	

**Notes :**

a.Pulse Test : Pulse Width &lt; 300μs, Duty Cycle ≤2%.

b.Guaranteed by design, not subject to production testing.

## Typical Electrical and Thermal Characteristics




Figure 1:Switching Test Circuit






Figure 2:Switching Waveforms




T<sub>J</sub>-Junction Temperature(°C)

Figure 3 Power Dissipation




T<sub>J</sub>-Junction Temperature(°C)

Figure 4 Drain Current



V<sub>DS</sub> Drain-Source Voltage (V)


Figure 5 Output Characteristics




I<sub>D</sub>- Drain Current (A)

Figure 6 Drain-Source On-Resistance


# SI2302




**Figure 7 Transfer Characteristics**




**Figure 8 Drain-Source On-Resistance**




**Figure 9  $R_{DS(on)}$  vs  $V_{GS}$**





**Figure 10 Capacitance vs  $V_{DS}$**




**Figure 11 Gate Charge**



**Figure 12 Source-Drain Diode Forward**



**Figure 13 Safe Operation Area**

**Figure 14 Normalized Maximum Transient Thermal Impedance**

### SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

### SOT-23 Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.05\text{mm}$ .
3. The pad layout is for reference purposes only.