

Egg-shaped Bicolor LED (Direct Mount)

SML70055 Series

External Dimensions (Unit: mm)



Directivity (Typical)



Absolute maximum ratings (Ta=25°C)

Symbol	Unit	Rating	Condition
I_F	mA	30	
ΔI_F	mA/°C	−0.45	Above 25°C
I_{FP}	mA	100	f=1kHz, tw≤100μs
V_R	V	4	
Top	°C	−30 to +85	
Tstg	°C	−30 to +100	

Electrical Optical characteristics (Ta=25°C)

●Common cathode (Internal wiring diagram 1)

Emitting color	Part Number	Lens color	Forward voltage V_F (V) typ	Forward voltage V_F (V) max	Condition I_F (mA)	Reverse current I_R (μA) max	Condition V_R (V)	Intensity I_V (mcd) typ	Condition I_F (mA)	Peak wavelength λP (nm) typ	Condition I_F (mA)	Spectrum half width Δλ (nm) typ	Condition I_F (mA)	Chip material
A Ultra-high-intensity red	SMLU72755C	Clear	2.0	2.5	10	10	4	160	20	635	10	15	10	AlGaInP
B Ultra-high-intensity yellow			2.0	2.5	10	10	4	170	20	572	10	15	10	AlGaInP
A Red	SML72755C	Clear	1.9	2.5	10	10	4	45	20	630	10	35	10	GaAsP
B Yellow			2.0	2.5	10	10	4	75	20	570	10	30	10	GaP
A Ultra-high-intensity amber	SMLU78755C	Clear	2.0	2.5	10	10	4	280	20	615	10	15	10	AlGaInP
B Ultra-high-intensity yellow			2.0	2.5	10	10	4	170	20	572	10	15	10	AlGaInP
A Orange	SML79255C	Clear	1.9	2.5	10	10	4	40	20	587	10	33	10	GaAsP
B Red			2.0	2.5	10	10	4	45	20	630	10	35	10	GaAsP
A Orange	SML79455C	Clear	1.9	2.5	10	10	4	45	20	587	10	33	10	GaAsP
B Green			2.0	2.5	10	10	4	75	20	560	10	20	10	GaP

●Common anode (Internal wiring diagram 2)

Emitting color	Part Number	Lens color	Forward voltage V_F (V) typ	Forward voltage V_F (V) max	Condition I_F (mA)	Reverse current I_R (μA) max	Condition V_R (V)	Intensity I_V (mcd) typ	Condition I_F (mA)	Peak wavelength λP (nm) typ	Condition I_F (mA)	Spectrum half width Δλ (nm) typ	Condition I_F (mA)	Chip material
A High-intensity red	SML76755WN	Diffused white	1.7	2.2	10	10	4	50	20	660	10	30	10	GaAlAs
B Yellow			2.4	3.0	10	10	4	50	20	570	10	30	10	GaP