WON-TOP ELECTRONICS


TC2520 & TC2524

25A GLASS PASSIVATED AVALANCHE 5/16" TIN CAN PRESS-FIT DIODE

RoHS Pb

Features

- Glass Passivated Die Construction
- Low Leakage
- Low Cost
- High Surge Current Capability
- Typical I_R less than 200nA



Tin Can		
Dim	**Min**	**Max**
A	8.67	8.77
B	7.10	7.30
C	10.40	10.60
D	1.40	1.60
E	26.00	—
All Dimensions in mm		

Mechanical Data

- Case: All Copper Case and Components Hermetically Sealed
- Terminals: Contact Areas Readily Solderable
- Polarity: Cathode to Case (Reverse Units Are Available Upon Request and Are Designated By A "R" Suffix, i.e. TC2520R or TC2524R)
- Polarity: Red Color Equals Standard, Black Color Equals Reverse Polarity
- Mounting Position: Any
- **Lead Free: For RoHS / Lead Free Version, Add "-LF" Suffix to Part Number, See Page 2**

Maximum Ratings and Electrical Characteristics @T_A=25°C unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Characteristic	Symbol	TC2520	TC2524	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	16	20	V
Average Rectified Output Current @T_C = 150°C	I_O	25		A
Breakdown Voltage Min. @I_R = 100mA Breakdown Voltage Max. @I_R = 100mA	V_{BR}	20 26	24 32	V
Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	300		A
Forward Voltage @I_F = 25A	V_{FM}	1.0		V
Peak Reverse Current At Rated DC Blocking Voltage @T_A = 25°C	I_{RM}	200		nA
Typical Junction Capacitance (Note 1)	C_J	300		pF
Typical Thermal Resistance (Note 2)	$R_{\theta JC}$	1.2		°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-65 to +175		°C

Note: 1. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.
2. Thermal Resistance: Junction to case, single side cooled.

© Won-Top Electronics Co., Ltd.

WON-TOP ELECTRONICS

ORDERING INFORMATION

Product No.	Package Type	Shipping Quantity
TC2520	5/16” Tin Can Press-Fit	500 Units/Box
TC2524	5/16” Tin Can Press-Fit	500 Units/Box

1. Shipping quantity given is for minimum packing quantity only. For minimum order quantity, please consult the Sales Department.
2. **To order Lead Free version (with Lead Free finish), add “-LF” suffix to part number above. For example, TC2520-LF.**

WON-TOP ELECTRONICS and are registered trademarks of Won-Top Electronics Co., Ltd (WTE). WTE has checked all information carefully and believes it to be correct and accurate. However, WTE cannot assume any responsibility for inaccuracies. Furthermore, this information does not give the purchaser of semiconductor devices any license under patent rights to manufacturer. WTE reserves the right to change any or all information herein without further notice.

WARNING: DO NOT USE IN LIFE SUPPORT EQUIPMENT. WTE power semiconductor products are not authorized for use as critical components in life support devices or systems without the express written approval.

Won-Top Electronics Co., Ltd.
No. 44 Yu Kang North 3rd Road,
Chine Chen Dist., Kaohsiung 806, Taiwan
Phone: 886-7-822-5408 or 886-7-822-5410
Fax: 886-7-822-5417
Email: sales@wontop.com
Internet: http://www.wontop.com

We power your everyday.

© Won-Top Electronics Co., Ltd.