


ZWD225PAF-0524/TA



Sales Region	Worldwide
Series	ZWD-PAF
Status	Production
Feature	Peak power capability
Option	With cover type With terminal (Vertical) type
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	83% Typ.
Rated Output Voltage[DC]	<u>5V</u> <u>24V</u>
Output Voltage Range[DC]	<u>4.5 to 5.5V</u> <u>22.8 to 27.6V</u>
Minimum Output Current	
Maximum Output Current	<u>5A</u> <u>9A</u>
Maximum Average Current	
Maximum Peak Current	
Total Maximum(Average) Output Power	225W
Total Maximum Peak Power	440W

Cases Shape & Size

Case'□' shape	PC board
Width(W)	108mm Nom.
Height(H)	58mm Nom.
Depth(D)	252mm Nom.
Weight	1065g Typ.

Other

Operating Temp. Range	-10 to 60°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
	EN50178
Safety Standard(Conformed)	Den-an

