

# LAMINATED TRANSFORMERS

## Type EI48 / 16.8 - 10VA









**AGENCY APPROVALS** 

1. UL 506, File E113449  **us**


3. EN61558  

Primary (V)	Secondary (V / mA)	No-Load Voltage (V)	Schematic No.	Part Number	Agency Approvals
230	6 / 1666	7.90	1	<b>048-5381.0</b>	1/3*
230	9 / 1111	12.00	1	<b>048-5382.0</b>	1/3*
230	12 / 834	15.70	1	<b>048-5383.0</b>	1/3*
230	15 / 666	19.20	1	<b>048-5384.0</b>	1/3*
230	18 / 555	22.90	1	<b>048-5385.0</b>	1/3*
230	24 / 416	30.60	1	<b>048-5386.0</b>	1/3*
230	2x6 / 834	2x7.90	2	<b>048-5387.0</b>	1/3*
230	2x9 / 555	2x12.00	2	<b>048-5388.0</b>	1/3*
230	2x12 / 416	2x15.70	2	<b>048-5389.0</b>	1/3*
230	2x15 / 333	2x19.20	2	<b>048-5390.0</b>	1/3*

-  Frequency 50/60Hz
-  Potted under vacuum
-  Split-bobbin
-  Temperature class ta 40°C/B
-  Weight: 0.295kg
-  Packaging unit: 10 pieces (tray)

\*NOTE: When checking the approval status of this product with VDE, add the prefix "BV" and the suffix "H" to the orderable Part Number (these letters will also be found on the part label). **The prefix and suffix are not part of the orderable Part Number.**

### Mechanical



### Schematics

