



SPECIFICATIONS

FREQUENCY RANGE: 2.0-8.0 GHz
 COUPLING (INCLUDES FREQUENCY SENSITIVITY): 6 ± 1.00 dB
 FREQUENCY SENSITIVITY: ± 0.50 dB
 INSERTION LOSS: (EXCLUDING COUPLED POWER) 0.50 dB (TRUE) 2.20 dB
 DIRECTIVITY: 20 dB MINIMUM
 PRIMARY LINE: 1.25 VSWR MAX.
 SECONDARY LINE: 1.25 VSWR MAX.
 AVG. INCIDENT: 50 WATTS POWER
 AVG. REFLECTED: 2 WATTS POWER



PASTERNAK ENTERPRISES, INC.

P.O BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com

COAXIAL & FIBER OPTICS

DWG TITLE

PE2210-6

DES.

SMA FEMALE DIRECTIONAL COUPLER
BROADBAND FREQUENCY RANGE: 2.0-8.0 GHz

REV. B

FSCM NO. 53919

CAD FILE 122111

SCALE N/A

SIZE A

2233

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].