

ACT1210-101-2P-TL00









用途	车载等级
特点	Wire Wound 绕线 AEC-Q200 AEC-Q200
系列	ACT
状态	量产体制
品牌	TDK



	尺寸
长度(L)	3.20mm ±0.20mm
宽度(W)	$2.50 \text{mm} \pm 0.20 \text{mm}$
厚度 高低	2.50mm Max.

电气特性		
共模阻抗[Typ.]	$5.1 \mathrm{k}\Omega$ at $10 \mathrm{MHz}$	
共模阻抗 [Min.]	$2.2k\Omega$ at 10MHz	
共模电感	100 μ H +50, -30% at 100kHz	
额定电流	150mA	
额定电压	80VDC	
绝缘电阻 [Min.]	10ΜΩ	
直流电阻	1.5Ω Max.	

;	其他
使用温度范围	-55∼150° C
阳校子汁	回流
焊接方法	烙铁焊接
AEC-Q200	Yes
包装形式	塑封编带 (330mm卷筒、帯宽 12mm)
包装个数	6000pcs
重量	0. 075g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website. ! All specifications are subject to change without notice.

ACT1210-101-2P-TL00









特性图表(这是参考数据,并不保证产品的特性。)









[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

ACT1210-101-2P-TL00












Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.