


ZWS150BAF-48/R



Sales Region	Worldwide
Series	ZWS-BAF
Status	Production
Feature	
Option	Remote ON/OFF control
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	91% Typ.
Rated Output Voltage[DC]	48V
Output Voltage Range[DC]	39.5 to 52.8V
Maximum Output Current	3.2A
Maximum Output Power	153.6W

Cases Shape & Size

Case'□ shape	PC board
Width(W)	75mm Nom.
Height(H)	37mm Nom.
Depth(D)	160mm Nom.
Weight	390g Typ.

Other

Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
Safety Standard(Conformed)	EN50178 (OV II)
	Den-an
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.