Product data sheet
Characteristics

HLA36060U31X6
Circuit breaker, PowerPacT H, Micrologic 3.2, I-Line, 60A, 3 pole, 50 kA, 600 VAC, phase CBA, 80% rated

Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip Unit Type	Electronic, standard, Micrologic 3.2, LI
Breaking capacity code	L

Complementary

Line Rated Current	60 A
Number of Poles	3P
Interrupt Rating	125 kA 240 V AC 100 kA 480 V AC 50 kA 600 V AC
[Ue] rated operational voltage	600 V AC
Continuous current rating	80 %
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
Wire Gauge	AWG 14...AWG 3/0 aluminium/copper
Phase	CBA
Height	9.73 in (247.14 mm)
Width	4.48 in (113.79 mm)
Depth	4.36 in (110.74 mm)
Tightening torque	44.25 lbf.in (5 N.m) 0.00…0.15 in² (2.5…95 mm²) AWG 14...AWG 3/0)

Environment

Product certifications	CCC CE CSA UL Listed IEC
Ambient air temperature for operation	104 °F (40 °C)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications