STGW75M65DF2, STGWA75M65DF2

Trench gate field-stop IGBT, M series 650 V, 75 A low loss

Datasheet - production data





Figure 1: Internal schematic diagram



Features

- 6 µs of short-circuit withstand time
- $V_{CE(sat)}$ = 1.65 V (typ.) @ I_C = 75 A
- Tight parameter distribution
- Safer paralleling
- Low thermal resistance
- Soft and very fast recovery antiparallel diode

Applications

- Motor control
- UPS
- PFC

Description

These devices are IGBTs developed using an advanced proprietary trench gate field-stop structure. The devices are part of the M series IGBTs, which represent an optimal balance between inverter system performance and efficiency where low-loss and short-circuit functionality are essential. Furthermore, the positive $V_{CE(sat)}$ temperature coefficient and tight parameter distribution result in safer paralleling operation.

Table 1: Device summary

Order code	Marking	Package	Packing
STGW75M65DF2	G75M65DF2	TO-247	Tube
STGWA75M65DF2		TO-247 long leads	

This is information on a product in full production.

www.st.com

Contents

1 Electrical ratings 3
2 Electrical characteristics 4
2.1 Electrical characteristics(curves) 6
3 Test circuits 11
4 Package information 12
4.1 TO-247 package information 12
4.2 TO-247 long leads package information 14
5 Revision history 16

1 Electrical ratings

Table 2: Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{CES}	Collector-emitter voltage (V_{GE} = 0)	650	V
I_C(1)	Continuous collector current at T_C = 25 °C	120	A
I_C	Continuous collector current at T_C = 100 °C	75	A
I_{CP}(2)	Pulsed collector current	225	A
V_{GE}	Gate-emitter voltage	±20	V
I_F(1)	Continuous forward current at T_C = 25 °C	120	A
I_F	Continuous forward current at T_C = 100 °C	75	A
I_{FP}(2)	Pulsed forward current	225	A
P_{TOT}	Total dissipation at T_C = 25 °C	468	W
T_{STG}	Storage temperature range	- 55 to 150	°C
T_J	Operating junction temperature range	- 55 to 175	°C

Notes:

(1)Current level is limited by bond wires

(2)Pulse width limited by maximum junction temperature.

Table 3: Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance junction-case IGBT	0.32	°C/W
R_{thJC}	Thermal resistance junction-case diode	0.74	°C/W
R_{thJA}	Thermal resistance junction-ambient	50	°C/W

2 Electrical characteristics

T_C = 25 °C unless otherwise specified

Table 4: Static characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)CES}$	Collector-emitter breakdown voltage	V_{GE} = 0 V, I_C = 1 mA	650			V
$V_{CE(sat)}$	Collector-emitter saturation voltage	V_{GE} = 15 V, I_C = 75 A		1.65	2.1	V
		V_{GE} = 15 V, I_C = 75 A, T_J = 125 °C		1.95		
		V_{GE} = 15 V, I_C = 75 A, T_J = 175 °C		2.1		
V_F	Forward on-voltage	I_F = 75 A		2		V
		I_F =75 A, T_J = 125 °C		1.75		
		I_F = 75 A, T_J = 175 °C		1.6		
$V_{GE(th)}$	Gate threshold voltage	V_{CE} = V_{GE}, I_C = 2 mA	5	6	7	V
I_{CES}	Collector cut-off current	V_{CE} = 0 V, V_{CE} = 650 V			25	µA
I_{GES}	Gate-emitter leakage current	V_{CE} = 0 V, V_{GE}= ± 20 V			±250	µA

Table 5: Dynamic characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{ies}	Input capacitance	V_{CE} = 25 V, f = 1 MHz, V_{GE} = 0 V	-	6290	-	pF
C_{oes}	Output capacitance		-	390	-	
C_{res}	Reverse transfer capacitance		-	136	-	
Q_g	Total gate charge	V_{CC} = 520 V, I_C = 75 A, V_{GE} = 15 V (see *Figure 30: " Gate charge test circuit"*)	-	225	-	nC
Q_{ge}	Gate-emitter charge		-	53	-	
Q_{gc}	Gate-collector charge		-	87	-	

Table 6: IGBT switching characteristics (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{CE} = 400 V, I_C = 75 A, V_{GE} = 15 V, R_G = 3.3 Ω (see *Figure 29: " Test circuit for inductive load switching"*)		47	-	ns
t_r	Current rise time			22.4	-	ns
$(di/dt)_{on}$	Turn-on current slope			2680	-	A/µs
$t_{d(off)}$	Turn-off-delay time			125	-	ns
t_f	Current fall time			93	-	ns
E_{on}(1)	Turn-on switching energy			0.69	-	mJ
E_{off}(2)	Turn-off switching energy			2.54	-	mJ
E_{ts}	Total switching energy			3.23	-	mJ
$t_{d(on)}$	Turn-on delay time	V_{CE} = 400 V, I_C = 75 A, V_{GE} = 15 V, R_G = 3.3 Ω T_J = 175 °C (see *Figure 29: " Test circuit for inductive load switching"*)		48	-	ns
t_r	Current rise time			25	-	ns
$(di/dt)_{on}$	Turn-on current slope			2420	-	A/µs
$t_{d(off)}$	Turn-off-delay time			125	-	ns
t_f	Current fall time			167	-	ns
E_{on}(1)	Turn-on switching energy			2.17	-	mJ
E_{off}(2)	Turn-off switching energy			3.45	-	mJ
E_{ts}	Total switching energy			5.62	-	mJ
t_{sc}	Short-circuit withstand time	V_{CC} ≤ 400 V, V_{GE} = 13 V, T_{Jstart} ≤ 150 °C	10		-	µs
		V_{CC} ≤ 400 V, V_{GE} = 15 V, T_{Jstart} ≤ 150 °C	6			

Notes:

(1)Including the reverse recovery of the diode.

(2)Including the tail of the collector current.

Table 7: Diode switching characteristics (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
t_{rr}	Reverse recovery time	I_F = 75 A, V_R = 400 V, V_{GE} = 15 V (see *Figure 29: " Test circuit for inductive load switching"*) di/dt = 1000 A/µs	-	165	-	ns
Q_{rr}	Reverse recovery charge		-	1.72	-	µC
I_{rrm}	Reverse recovery current		-	25	-	A
dI_{rr}/dt	Peak rate of fall of reverse recovery current during t_b		-	750	-	A/µs
E_{rr}	Reverse recovery energy		-	289	-	µJ
t_{rr}	Reverse recovery time	I_F = 75 A, V_R = 400 V, V_{GE} = 15 V T_J = 175 °C (see *Figure 29: " Test circuit for inductive load switching"*) di/dt = 1000 A/µs	-	256	-	ns
Q_{rr}	Reverse recovery charge		-	6.85	-	µC
I_{rrm}	Reverse recovery current		-	48	-	A
dI_{rr}/dt	Peak rate of fall of reverse recovery current during t_b		-	300	-	A/µs
E_{rr}	Reverse recovery energy		-	1033	-	µJ

2.1 Electrical characteristics(curves)

Figure 2: Power dissipation vs. case temperature




Figure 3: Collector current vs. case temperature




Figure 4: Output characteristics (TJ = 25 °C)




Figure 5: Output characteristics (TJ = 175 °C)




Figure 6: VCE(sat) vs. junction temperature




Figure 7: VCE(sat) vs. collector current




Figure 8: Collector current vs. switching frequency




Figure 9: Forward bias safe operating area




Figure 10: Transfer characteristics




Figure 11: Diode VF vs. forward current




Figure 12: Normalized VGE(th) vs. junction temperature




Figure 13: Normalized V(BR)CES vs. junction temperature




Figure 14: Capacitance variations




Figure 15: Gate charge vs. gate-emitter voltage




Figure 16: Switching energy vs. collector current




Figure 17: Switching energy vs. gate resistance




Figure 18: Switching energy vs. temperature




Figure 19: Switching energy vs. collector emitter voltage




Figure 20: Short-circuit time and current vs. VGE




Figure 21: Switching times vs. collector current




Figure 22: Switching times vs. gate resistance




Figure 23: Reverse recovery current vs. diode current slope




Figure 24: Reverse recovery time vs. diode current slope




Figure 25: Reverse recovery charge vs. diode current slope




Figure 26: Reverse recovery energy vs. diode current slope




Figure 27: Thermal impedance for IGBT





Figure 28: Thermal impedance for diode



3 Test circuits

Figure 29: Test circuit for inductive load switching




Figure 30: Gate charge test circuit




Figure 31: Switching waveform





Figure 32: Diode reverse recovery waveform



4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: ***www.st.com***. ECOPACK® is an ST trademark.

4.1 TO-247 package information

Figure 33: TO-247 package outline




Table 8: TO-247 package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.85		5.15
A1	2.20		2.60
b	1.0		1.40
b1	2.0		2.40
b2	3.0		3.40
c	0.40		0.80
D	19.85		20.15
E	15.45		15.75
e	5.30	5.45	5.60
L	14.20		14.80
L1	3.70		4.30
L2		18.50	
ØP	3.55		3.65
ØR	4.50		5.50
S	5.30	5.50	5.70

4.2 TO-247 long leads package information

Figure 34: TO-247 long lead package outline




Table 9: TO-247 long lead package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.90	5.00	5.10
A1	2.31	2.41	2.51
A2	1.90	2.00	2.10
b	1.16		1.26
b2			3.25
b3			2.25
c	0.59		0.66
D	20.90	21.00	21.10
E	15.70	15.80	15.90
E2	4.90	5.00	5.10
E3	2.40	2.50	2.60
e	5.34	5.44	5.54
L	19.80	19.92	20.10
L1			4.30
P	3.50	3.60	3.70
Q	5.60		6.00
S	6.05	6.15	6.25

5 Revision history

Table 10: Document revision history

Date	Revision	Changes
02-Dec-2015	1	First release.
15-Jun-2016	2	Inserted device in TO-247 and document updated accordingly. Inserted *Section 2.1: "Electrical characteristics(curves)"*. Document status promoted from preliminary to production data. Minor text changes.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2016 STMicroelectronics – All rights reserved