


<b>Sales Region</b>	Worldwide (except Japan)
<b>Series</b>	ALE
<b>Model</b>	ALE-OEM
<b>Status</b>	 Production
<b>Option</b>	Negative polarity
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	180 to 254Vac
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	4000Vdc
Output Voltage Range[DC]	0 to 4000V
Average Capacitor Charging Power	1500J/sec
Peak Capacitor Charging Power	1650J/sec
Charge Current	825mA
Continuous DC Current	375mA
Continuous DC Power	1.5kW
Polarity	Negative
Power Factor	0.65
Efficiency	85% Typ.

### Package Type & Size

Package / Mounting	Enclosed / Unit type
Width(W)	146mm Nom. (5.75in Nom.)
Height(H)	141mm Nom. (5.55in Nom.)
Depth(D)	361mm Nom. (14.21in Nom.)
Weight	4000g Typ. (8.8lbs Typ.)

### Other

Operating Temp. Range	-20 to 45°C
Storage Temp. Range	-40 to 85°C
Cooling	Forced air
Safety Standard(Certified)	IEC60601-1
	EN60601-1
	UL60601-1

### Safety Standard(Conformed)

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.