

## IE-SWM-SL04-4SCS

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



### Features of SubstationLine managed switch series

The SubstationLine includes Ethernet switches complying with the IEC 61850-3 and IEEE 1613 standards, making them robust enough for operation in harsh environments. The family includes variants for mounting on DIN rails and in 19" racks.

All products have a redundant power supply to ensure reliability in critical environments. The new family ranges from managed Fast Ethernet switches to 10-Gigabit Ethernet products with all the necessary features to operate according to the most demanding requirements.

- DIN-rail and 19" rack variants
- IEC 61850-3 and IEEE 1613 compliance
- Redundant power supply modules in all models
- Wide operating temperature range of -40°C up to 85°C
- Modular switch version with high flexibility in number and type of ports
- Fast/Gigabit/10-Gigabit interfaces

### General ordering data

Version	Media interface module for modular switch, Fast Ethernet, Number of ports: 4x SC Single-mode, -40 °C...85 °C
Order No.	<a href="#">2779160000</a>
Type	IE-SWM-SL04-4SCS
GTIN (EAN)	4064675048527
Qty.	1 pc(s).

**IE-SWM-SL04-4SCS**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	107 mm	Depth (inches)	4.213 inch
Height	40.7 mm	Height (inches)	1.602 inch
Width	99 mm	Width (inches)	3.898 inch
Net weight	425 g		

**Temperatures**

Storage temperature	-40 °C...85 °C	Operating temperature	-40 °C...85 °C
Humidity	5 to 95 % (non-condensing)		

**Environmental conditions**

Humidity	5 to 95 % (non-condensing)	Operating altitude	≤ 2000 m
Operating temperature, max.	85 °C	Operating temperature, min.	-40 °C
Storage temperature, max.	85 °C	Storage temperature, min.	-40 °C

**Fibre optic transceiver characteristics**

Transmission rate	100 MBit/s		
Transceiver type	Singlemode		
Connector type	SC-Duplex		
Transmission distance, typ.	30 km		
Wavelength	typ.	1,310 nm	
Receive power	min.	-34 dBm	
	max.	0 dBm	
Transmission power	min.	-15 dBm	
	max.	-8 dBm	
Link-budget	19 dB		

**Guarantee**

Time interval	5 years
---------------	---------

**Interfaces**

Fibre-optic ports	100BaseFX ports (SC connector), Singlemode	Number of ports	4x SC Single-mode
-------------------	--	-----------------	-------------------

**MTBF**

MTBF	According to Standard	Telcordia SR-332
	Operating time (hours), min.	401,287 hrs

**Power supply**

Voltage supply	via Ethernet switch
----------------	---------------------

**Technical data**

Housing main material	Metal	Speed	Fast Ethernet
Type of mounting	Insert in module slot		

Creation date November 4, 2021 1:31:03 AM CET

## IE-SWM-SL04-4SCS

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

# Technical data

### Classifications

ETIM 6.0	EC000309	ETIM 7.0	EC000309
ETIM 8.0	EC000309	ECLASS 9.1	19-17-03-90
ECLASS 10.0	19-17-04-90	ECLASS 11.0	19-17-03-03

### Approvals

ROHS	Conform
------	---------

### Downloads

Approval/Certificate/Document of Conformity	<a href="#">EU Declaration of Conformity</a> <a href="#">RCM Declaration of Conformity</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>