

ZUP120-1.8/L



Sales Region	Worldwide
Series	ZUP
Type	200W Model
Status	 Production
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics	
Input Voltage[AC]	Single-phase 100V/200V
Input Voltage Range[AC]	85 to 265V
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	120V
Output Voltage[DC]	0 to 120V
Rated Output Current	1.8A
Output Current	0 to 1.8A
Rated Output Power	216W
Efficiency	82% Typ.
Voltage Ripple Noise	0.02Vrms (5Hz to 1MHz)
Current Ripple Noise	0.005Arms (5Hz to 1MHz)

Cases Shape & Size	
Case'□ shape	Bench top
Width(W)	70mm Nom.
Height(H)	153mm Nom.
Depth(D)	405.9mm Nom.
Weight	2900g Typ.

Other	
Interface Option	Front panel output jacks
Operating Temp. Range	0 to 50°C
Safety Standard(Certified)	CSA C22.2 No.1010.1-92 EN61010-1 UL3111-1
Safety Standard(Conformed)	

Remarks This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.