
FEATURES

- **Max. propagation delay of 700ps**
- **I_{EE} min. of –55mA**
- **Extended supply voltage option: V_{EE} = –4.2V to –5.5V**
- **Voltage and temperature compensation for improved noise immunity**
- **Internal 75KΩ input pull-down resistors**
- **70% faster than Fairchild 300K at lower power**
- **Function and pinout compatible with Fairchild F100K**
- **Available in 24-pin CERPACK and 28-pin PLCC packages**


BLOCK DIAGRAM




DESCRIPTION

The SY100S322 is an ultra-fast buffer designed for use in high-performance ECL systems. The device provides nine non-inverting buffers with single-ended outputs. The inputs on the device have 75KΩ pull-down resistors.

PIN CONFIGURATIONS





PIN NAMES

Pin	Function
D_1 – D_9	Data Inputs
O_1 – O_9	Data Outputs
V_{EES}	V_{EE} Substrate
V_{CCA}	V_{CCO} for ECL Outputs

LOGIC EQUATION

$O_n = D_n$, n = 1 to 9

DC ELECTRICAL CHARACTERISTICS

V_{EE} = –4.2V to –5.5V unless otherwise specified, $V_{CC} = V_{CCA}$ = GND

Symbol	Parameter	Min.	Typ.	Max.	Unit	Condition
I_{IH}	Input HIGH Current	—	—	200	µA	$V_{IN} = V_{IH}$ (Max.)
I_{EE}	Power Supply Current	–55	–41	–25	mA	Inputs Open

AC ELECTRICAL CHARACTERISTICS

CERPACK

V_{EE} = –4.2V to –5.5V unless otherwise specified, $V_{CC} = V_{CCA}$ = GND


Symbol	Parameter	T_A = 0°C		T_A = +25°C		T_A = +85°C		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.		
t_{PLH} t_{PHL}	Propagation Delay Data to Output	300	800	300	800	300	800	ps	
t_{TLH} t_{THL}	Transition Time 20% to 80%, 80% to 20%	300	900	300	900	300	900	ps	

PLCC

V_{EE} = –4.2V to –5.5V unless otherwise specified, $V_{CC} = V_{CCA}$ = GND

Symbol	Parameter	T_A = 0°C		T_A = +25°C		T_A = +85°C		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.		
t_{PLH} t_{PHL}	Propagation Delay Data to Output	300	700	300	700	300	700	ps	
t_{TLH} t_{THL}	Transition Time 20% to 80%, 80% to 20%	300	900	300	900	300	900	ps	

TIMING DIAGRAM




Propagation Delay and Transition Times

NOTE:
V_{EE} = –4.2V to –5.5V unless otherwise specified, V_{CC} = V_{CCA} = GND

PRODUCT ORDERING CODE

Ordering Code	Package Type	Operating Range
SY100S322FC	F24-1	Commercial
SY100S322JC	J28-1	Commercial
SY100S322JCTR	J28-1	Commercial


24 LEAD CERPACK (F24-1)



NOTES:
1. DIMENSIONS ARE IN INCHES[MM].
2. THIS DIMENSION INCLUDES GLASS PROTRUSION AND CAP TO BASE ALIGNMENT TOLERANCES.
3. DIMENSIONS SHOWN ARE MAX/MIN, WHERE NOTED.

Rev. 03

28 LEAD PLCC (J28-1)



NOTES:
1. DIMENSIONS ARE IN INCHES[MM].
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008[0.203].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. 03

MICREL-SYNERGY 3250 SCOTT BOULEVARD SANTA CLARA CA 95054 USA

TEL + 1 (408) 980-9191 FAX + 1 (408) 914-7878 WEB http://www.micrel.com

This information is believed to be accurate and reliable, however no responsibility is assumed by Micrel for its use nor for any infringement of patents or other rights of third parties resulting from its use. No license is granted by implication or otherwise under any patent or patent right of Micrel Inc.

© 2000 Micrel Incorporated