FAIRCHILD
SEMICONDUCTOR TM

MPSW3725



TO-226

NPN Transistor

This device is designed for high current, low impedance line driver applications. Sourced from Process 26.

Absolute Maximum Ratings

TA = 25°C unless otherwise noted

Symbol	Parameter	Value	Units
V_{CEO}	Collector-Emitter Voltage	40	V
V_{CBO}	Collector-Base Voltage	60	V
V_{EBO}	Emitter-Base Voltage	6.0	V
I_C	Collector Current - Continuous	1.2	A
T_J, T_{stg}	Operating and Storage Junction Temperature Range	-55 to +150	°C

*These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

NOTES:
1) These ratings are based on a maximum junction temperature of 150 degrees C.
2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Thermal Characteristics

TA = 25°C unless otherwise noted

Symbol	Characteristic	Max	Units
		MPSW3725	
P_D	Total Device Dissipation Derate above 25°C	1.0 8.0	W mW/°C
$R_{\theta JC}$	Thermal Resistance, Junction to Case	125	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	50	°C/W

© 1999 Fairchild Semiconductor Corporation

NPN Transistor
(continued)

Electrical Characteristics
TA= 25°C unless otherwise noted


Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
OFF CHARACTERISTICS						
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage*	I_C = 10 mA, I_B = 0	40			V
$V_{(BR)CES}$	Collector-Emitter Breakdown Voltage	I_C = 10 µA, V_{BE} = 0	60			V
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	I_C = 100 µA, I_{CE} = 0	60			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	I_E = 10 µA, I_C = 0	6.0			V
I_{CBO}	Collector Cutoff Current	V_{CB} = 50 V, I_E = 0 V_{CB} = 50 V, I_E = 0, T_A = 100°C			100 10	nA µA
ON CHARACTERISTICS*						
h_{FE}	DC Current Gain	I_C = 10 mA, V_{CE} = 1.0 V I_C = 100 mA, V_{CE} = 1.0 V I_C=100mA,V_{CE}=1.0V,T_A=-55°C I_C = 300 mA, V_{CE} = 1.0 V I_C = 500 mA, V_{CE} = 1.0 V I_C=500mA,V_{CE}=1.0V,T_A=-55°C I_C = 800 mA, V_{CE} = 2.0 V I_C = 1.0 A, V_{CE} = 5.0 V	30 60 30 40 35 20 20 25		 180	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	I_C = 10 mA, I_B = 1.0 mA I_C = 100 mA, I_B = 10 mA I_C = 300 mA, I_B = 30 mA I_C = 500 mA, I_B = 50 mA I_C = 800 mA, I_B = 80 mA I_C = 1.0 A, I_B = 100 mA			0.25 0.26 0.4 0.52 0.8 0.95	V V V V V V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	I_C = 10 mA, I_B = 1.0 mA I_C = 100 mA, I_B = 10 mA I_C = 300 mA, I_B = 30 mA I_C = 500 mA, I_B = 50 mA I_C = 800 mA, I_B = 80 mA I_C = 1.0 A, I_B = 100 mA			0.76 0.86 1.1 1.2 1.5 1.7	V V V V V V
SMALL SIGNAL CHARACTERISTICS						
f_T	Current Gain - Bandwidth Product	I_C = 50 mA, V_{CE} = 10 V, f = 100 MHz	250			MHz
C_{obo}	Output Capacitance	V_{CB} = 10 V, I_E = 0, f = 1.0 MHz			25	pF
C_{ibo}	Input Capacitance	V_{EB} = 0.5 V, I_C = 0, f = 1.0 MHz			100	pF
SWITCHING CHARACTERISTICS						
t_{on}	Turn-on Time	V_{CC} = 30 V, V_{BE} = 3.8 V,		22		ns
t_d	Delay Time	I_C = 500 mA, I_{B1} = 50 mA		10		ns
t_r	Rise Time			12		ns
t_{off}	Turn-off Time	V_{CC} = 30 V, I_C = 500mA		250		ns
t_s	Storage Time	I_{B1} = I_{B2} = 50 mA		235		ns
t_f	Fall Time			15		ns

*Pulse Test: Pulse Width ≤ 300 µs, Duty Cycle ≤ 1.0%


NPN Transistor
(continued)

Typical Characteristics


Typical Pulsed Current Gain vs Collector Current




Collector-Emitter Saturation Voltage vs Collector Current




Base-Emitter Saturation Voltage vs Collector Current




Base-Emitter ON Voltage vs Collector Current



Collector-Cutoff Current vs Ambient Temperature




Input / Output Capacitance vs Reverse Bias




Typical Characteristics (continued)

Contours of Constant Bandwidth Product (f_T)




Power Dissipation vs Ambient Temperature




Typical Characteristics (continued)


Storage Time vs. Turn On and Turn Off Base Currents




Storage Time vs. Turn On and Turn Off Base Currents



Storage Time vs. Turn On and Turn Off Base Currents




Rise Time vs. Collector and Turn On Base Currents




Typical Characteristics (continued)


Fall Time vs. Turn On and Turn Off Base Currents



Fall Time vs. Turn On and Turn Off Base Currents



Fall Time vs. Turn On and Turn Off Base Currents



Test Circuit




FIGURE 1: Switching Time Test Circuit
(I_C = 500 mA, I_{B1} = 50 mA, I_{B2} = 50 mA)

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™
Bottomless™
CoolFET™
CROSSVOLT™
DOME™
E^2CMOS^{TM}
EnSigna™
FACT™
FACT Quiet Series™
FAST®
FASTr™
GlobalOptoisolator™
GTO™
HiSeC™
ISOPLANAR™
MICROWIRE™
OPTOLOGIC™
OPTOPLANAR™
PACMAN™
POP™
PowerTrench®
QFET™
QS™
QT Optoelectronics™
Quiet Series™
SILENT SWITCHER®
SMART START™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SyncFET™
TinyLogic™
UHC™
VCX™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.
As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.