





ohne Ansaughaube
without hood



Leiterplatten-Layout Vorschlag für SMT PCB-Layout Proposal for SMT




Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating


Anschlussbereich verzinnt 4-6 µm
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
Coplanarity Area of Termination ≤ 0,1 mm

Verpackt im Gurt in Anlehnung an DIN IEC 60286-3
Tape on Reel Packaging according to DIN IEC 60286-3
Verpackungseinheit: 320 Stück
Packaging unit: 320 pcs




← Abspulrichtung - Reel off Direction



Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16016 to be observed.

Proprietary notice pursuant to ISO 16016 to be observed.

Information: Codierung, grün - <i>coding, green</i>				Tolerances		 All Dimensions in mm		Scale 3:1		
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.				Subject to modification without prior notice. Drawing will not be updated.		Designation M 2,54 SRC-P, 3-polig				
						101904240001				
										www.ERNI.com
g		19.02.2016		Class SRCP						
Index		Date								