1. Dimensions:





CO-PLANARITY ± 0.004 Max / 0.10 Max



SUGGESTED FOOTPRINT

Notes:

1. Solderability: Leads shall meet MIL-STD-202, Method 208D for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +85°C
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Moisture Sensitivity: Level 2

DOC. REV. B/1

2. Schematic:



3. Electrical Specifications: @25°C

Isolation Voltage: 1500VAC

Insertion Loss: -1.0dB Maximum @1MHz-10MHz

Return Loss: -15dB Minimum @1MHz-10MHz

Crosstalk: -30dB Minimum @1MHz-10MHz

Attenuation @30MHz

Transmit	-28dB Minimum
Receive	-18dB Minimum

Cut-off Frequency: 17MHz Typical

I/O Impedance: 100 Ohms

XFMRS Inc	Title: 10BASE -T FILTER		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xxx ±0.010 Inch Dimensions in Inch/mm	P/N: XF20064CS3		REV. B
	DWN.	康玉坤	Jul-27-04
	CHK.	李清儿	Jul-27-04
SHEET 1 OF 1	APP.	BW	Jul-27-04

PROPRIETARY Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.