Product data sheet
Characteristics

DF141N
Fuse carrier TeSys DF, 1P+N 50A, fuse size 14x51 mm

Product availability : Non-Stock - Not normally stocked in distribution facility

Green Premium™

Price* : 57.00 USD



Main

Range	TeSys
Product name	TeSys DF
Product or component type	Fuse carrier
Device short name	DF14
Device composition	tubular link locked in Neutral pole
Product compatibility	DF2EA fuse cartridge DF2EN fuse cartridge
Poles description	1P + N
Fuse size	14 x 51 mm
Fuse type	, gG , aM
Control type	Toggle
[Ue] rated operational voltage	690 V AC 690 V DC
[Ie] rated operational current	50 A
[Ui] rated insulation voltage	690 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ipk] rated peak withstand current	15 kA with tubular links IEC 60269-1
Short-circuit withstand	120 kA 400 V IEC 60947-3 120 kA 500 V IEC 60947-3 80 kA 690 V IEC 60947-3

Complementary

Standards	EN/IEC 60947-3 EN/IEC 60269-2 UL 4248-1 CSA C22.2 No 4248-1

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	IEC UL Recognized CSA EAC
Mounting support	35 mm symmetrical DIN rail
Mounting position	Vertical +/- 23°)
Connections - terminals	screw clamp terminals 1 0.00…0.04 in² (2.5…25 mm²)rigid screw clamp terminals 2 0.00…0.02 in² (2.5…10 mm²)rigid screw clamp terminals 1 0.00…0.04 in² (2.5…25 mm²)flexible with or without screw clamp terminals 2 0.00…0.02 in² (2.5…10 mm²)flexible with or without
Tightening torque	30.98 lbf.in (3.5 N.m)
Height	4.36 in (110.8 mm)
Width	2.07 in (52.5 mm)
Depth	3.01 in (76.5 mm)
Net Weight	0.64 lb(US) (0.290 kg)
Quantity per set	Set of 3

Environment

Ambient air temperature for storage	-40…176 °F (-40…80 °C)
Ambient air temperature for operation	-4…140 °F (-20…60 °C) with derating above 20°C
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH
Fire resistance	1760 °F (960 °C) IEC 60695-2-1
Compatibility code	DF14

Ordering and shipping details

Category	21714 - DF FUSEHOLDERS
Discount Schedule	CP1
GTIN	03389119407397
Nbr. of units in pkg.	1
Package weight(Lbs)	9.31 oz (264 g)
Returnability	No
Country of origin	TN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.37 in (11.1 cm)
Package 1 width	3.03 in (7.7 cm)
Package 1 Length	2.09 in (5.3 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	3
Package 2 Weight	28.22 oz (800 g)
Package 2 Height	3.23 in (8.2 cm)
Package 2 width	6.77 in (17.2 cm)
Package 2 Length	4.65 in (11.8 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	36
Package 3 Weight	22.15 lb(US) (10.048 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer - www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months