



PE210G1SPI9A

Single Port SFP+ 10 Gigabit Ethernet PCI Express Server Adapter Intel® 82599ES Based

Product Description

Silicom's SFP+ 10 Gigabit Ethernet PCI Express server adapters are designed for Servers and high-end appliances.

The Silicom 10 Gigabit Ethernet PCI Express Server adapters offer simple integration into any PCI Express X8 to 10Gigabit Networks.

The performance is optimized so that system I/O is not the bottleneck in high-performance networking applications.

The Silicom SFP+ 10 Gigabit Ethernet PCI Express server adapters are based on Intel 82599ES Ethernet controller with fully integrated Gigabit Ethernet Media Access Control (MAC) and SFP port. In addition to managing MAC and PHY Ethernet layer functions, the controller manages PCI Express packet traffic across its transaction, link, and physical/logical layers. Using hardware acceleration, the controller offloads tasks from the host, such as TCP/UDP/IP checksum calculations and TCP segmentation.

Silicom's SFP+ 10 Gigabit Ethernet PCI-Express Server adapters are the ideal solution for implementing multiple network segments, mission-critical high-powered networking applications and environments within high performance servers

Key Features

SFP+ 10Gigabit Ethernet

10Gigabit Ethernet Adapter with SFP cage support:

-XR: Copper 10SFP+Cu (Passive Direct Attach Cable):

- Compliant with the SFP+ MSA SFF-8431 specification
- Up to 10 meters

-SR: Fiber 10 Gigabit Ethernet 10GBASE-SR:

- 10BASE-SR with 10Gigabit 850nm Small form Factor Pluggable (SFP+)

-LR: Fiber 10 Gigabit Ethernet 10GBASE-LR:

- 10BASE-LR with 10Gigabit 1310nm Small form Factor Pluggable (SFP+)

-SRD: Fiber 1/10 Gigabit Ethernet 1000Base-SX / 10GBASE-SR:

- 1000BASE-SX with 1G 850nm Small form Factor Pluggable (SFP+)
- 10GBASE-SR with 10Gigabit 850nm Small form Factor Pluggable (SFP+)

-LRD: Fiber 1/10 Gigabit Ethernet 1000Base-LX / 10GBASE-LR:

- 1000BASE-LX with 1G 1310nm Small form Factor Pluggable (SFP+)
- 10GBASE-LR with 10Gigabit 1310nm Small form Factor Pluggable (SFP+)

-SR: Fiber 10 Gigabit Ethernet 10GBASE-SR:

- 10 Gigabit Fiber Ethernet port supports 10GBASE-SR (850nm LAN PHY)
- 10Gigabit 850nm Small form Factor Pluggable (SFP+)

-LR: Fiber 10 Gigabit Ethernet 10GBASE-LR:

- 10 Gigabit Fiber Ethernet port supports 10GBASE-LR (1310nm LAN PHY)
- 10Gigabit 1310nm Small form Factor Pluggable (SFP+)

-SRD: Fiber 1/10 Gigabit Ethernet 1000Base-SX / 10GBASE-SR:

- 10 Gigabit Fiber Ethernet port supports 10GBASE-SR (850nm LAN PHY)
- 1Gigabit Fiber Ethernet port supports 1000BASE-SX (850nm LAN PHY)
- 1/10Gigabit 850nm Small form Factor Pluggable (SFP+)

-LRD: Fiber 1/10 Gigabit Ethernet 1000Base-LX / 10GBASE-LR:

- 10 Gigabit Fiber Ethernet port supports 10GBASE-LR (1310nm LAN PHY)
- 1Gigabit Fiber Ethernet port supports 1000BASE-LX (1310nm LAN PHY)
- 1/10Gigabit 1310nm Small form Factor Pluggable (SFP+)

Host Interface:

- PCI Express X8 lanes
- Support PCI Express Base Specification 2.0 (5GT/s)
- Low-Profile Adapter
- Low power
- SFP+ cage

Performance Features:

- IPV4 and IPV6 Supports for IP/ TCP and IP/UDP Receive Checksum offload
- Fragmented UDP checksum offload for Packet Reassembly
- CPU utilization- the 82599 supports reduction in CPU utilization, mainly by supporting Receive Side Coalescing (RSC).
- Support for 16 virtual machine Device Queues (VMDq) per port
- Support Direct Cache Access (DCA)

- Advanced memory architecture reduces latency by preceding TSO packets. A TSO packet may be interleaved with other packets going to the wire.
- Minimized device I/O interrupts using MSI and MSI-X
- Offload of TCP / IP / UDP checksum calculation and TCP segmentation
- Large on chip receive packet buffer (512 KB)
- Large on chip transmit packet buffer (160KB)
- Supports the VPD (Vital Product Data) capability defined in the PCI specification ver. 3.0
- Time sync- IEEE1588- Precision Time Protocol (PTP)
- Supports the BCN (Backward Congestion Notification) protocol in addition to the EEDC functionality

LAN Features:

- IEEE 802.x flow control support
- IEEE 802.1q VLAN tagging support
- IEEE 802.1p layer 2 priority encoding
- Jumbo Frame (up to 15.5KB)
- Link Aggregation and Load Balancing.
- RFC2819 RMON MIB statistics
- TCP Segmentation Offload Up to 256KB
- Ipv6 Support for IP/TCP Receive Checksum Offload
- LEDs indicator for link/Activity

SFP+ 10Gigabit Ethernet Technical Specifications Adapters:

- IEEE 802.x flow control support
- IEEE 802.q VLAN tagging support
- IEEE 802.1p layer 2 priority encoding
- Jumbo Frame (up to 16KB)
- Link Aggregation and Load Balancing
- RFC2819 RMON MIB statistics
- TCP Segmentation Offload Up to 256KB
- Ipv6 Support for IP/TCP Receive Checksum Offload
- DDP Offload
- LEDs indicator for link/Activity

Technical Specifications

SFP+ 10 Gigabit Ethernet Technical Specifications Adapters:

SFP+ (Small Form Factor Pluggable) supports:	SFI interfaces supports 10GBase-R PCS and 10 Gigabit PMA in order to connect with SFP+ to 10GBase-SR // 1000Base-SX / 10GBase-LR and SFP+ Direct Attach
10GBase-SR SFP+: IEEE Standard / Network topology:	Fiber 10Gigabit Ethernet, 10GBASE-SR (850nM LAN PHY)
10GBase-SR SFP+: Data Transfer Rate:	10.3125GBd
10GBase-SR SFP+: Cables and Operating distance Up to:	62.5um, 160MHz/Km 26m 62.5um, (OM1)200MHz/Km 33m 50um, 400MHz/Km 66m 50um, (OM2)500 MHz/Km 82m 50um, (OM3)2000MHz/Km 300m
10GBase-LR SFP+: IEEE Standard / Network topology:	Fiber 10Gigabit Ethernet, 10GBASE-LR (1310nM LAN PHY)
10GBase-LR SFP+: Data Transfer Rate:	10.3125GBd
10GBase-LR SFP+: Cables and Operating distance Up to:	Single-Mode: 10000m at 9um
10GSFP+Cu : IEEE Standard / Network topology:	Copper 10Gigabit Ethernet, 10GSFP+Cu (Direct Attach)
1000Base-SX / 10GBase-SR SFP+: IEEE Standard / Network topology:	Fiber Gigabit Ethernet, 1000Base-SX (850nM LAN PHY) Fiber 10Gigabit Ethernet, 10GBASE-SR (850nM LAN PHY)
1000Base-SX / 10GBase-SR SFP+: Data Transfer Rate:	10.3125GBd / 1.25GBd
10000Base-SX / 10GBase-	10000Base-SX:

SR SFP+: Cables and Operating distance Up to:	62.5um, 160MHz/Km 220m 62.5um, (OM1)200MHz/Km 275m 50um, 400MHz/Km 500m 50um, (OM2)500 MHz/Km 550m 50um, (OM3)2000MHz/Km >550m 10GBase-SR: 62.5um, 160MHz/Km 26m 62.5um, (OM1)200MHz/Km 33m 50um, 400MHz/Km 66m 50um, (OM2)500 MHz/Km 82m 50um, (OM3)2000MHz/Km 300m
1000Base-LX / 10GBase-LR SFP+: IEEE Standard / Network topology:	Fiber Gigabit Ethernet, 1000Base-LX (1310nM LAN PHY) Fiber 10Gigabit Ethernet, 10GBASE-LR (1310nM LAN PHY)
1000Base-LX / 10GBase-LR SFP+: Data Transfer Rate:	10.3125GBd / 1.25GBd
1000Base-LX / 10GBase-LR SFP+: Cables and Operating distance Up to:	10000Base-LX: Single-Mode: 5000m at 9um 10GBase-LR: Single-Mode: 10000m at 9um
-SR: Fiber 10GBASE-SR Ethernet Technical Specifications:	
Output Transmit Power:	Typical: -2.33 dBm Minimum: -2.8 dBm
Optical Receive Sensitivity:	Typical: -13.45 dBm Maximum: -11.1 dBm
Maximum Input Power:	Maximum: +0.5dBm
-LR: Fiber 10GBASE-LR Ethernet Technical Specifications:	
Output Transmit Power:	Typical: -2.75 dBm Minimum: -8.2 dBm
Optical Receive Sensitivity:	Typical: -14.65 dBm Maximum: -12.6 dBm

Maximum Input Power:	Maximum: +0.5dBm
-SRD: Fiber 1000BASE-SX / 10GBASE-SR Technical Specifications:	
Optical Output Power (1G):	Minimum: -9.5 dBm
Optical Receive Sensitivity (1G):	Maximum: -17 dBm
Maximum Input Power (1G):	Maximum: +0.5dBm
Output Transmit Power (10G):	Minimum: -5 dBm
Optical Receive Sensitivity (10G):	Maximum: -11.1 dBm
Maximum Input Power (10G):	Maximum: +0.5dBm
-LRD: Fiber 1000BASE-LX / 10GBASE-LR Technical Specifications:	
Optical Output Power (1G):	Minimum: -11 dBm
Optical Receive Sensitivity (1G):	Maximum: -19 dBm
Maximum Input Power (1G):	Maximum: +0.5dBm
Output Transmit Power (10G):	Minimum: -8.2 dBm
Optical Receive Sensitivity (10G):	Maximum: -12.5 dBm
Maximum Input Power (10G):	Maximum: +0.5dBm
Operating Systems Support	
Operating system support:	Windows Linux FreeBSD VMware

General Technical Specifications	
Interface Standard:	PCI-Express Base Specification Revision 2.0 (5GT/s)
Board Size:	Low profile add-in card: 167.65mm X 68.91mm (6.60"X 2.713")
PCI Express Card Type:	X8 Lane
PCI Express Voltage:	+12V +- 8%
PCI Connector:	X8 Lane
Controller:	Intel 82599ES
Holder:	Metal Bracket
Operating Humidity:	0%–90%, non-condensing
Operating Temperature:	0°C – 50°C (32°F – 122°F)
Storage:	-20°C–65°C (-4°F–149°F)
EMC Certifications:	<p>CE EN 55022: 1998 Class B Amendments A1: 2000; A2: 2003</p> <p>Conducted Emissions</p> <p>Radiated Emissions</p> <p>CE EN 55024: 1998 Amendments A1: 2000; A2: 2003</p> <p>Immunity for ITE Amendment A1: 2001</p> <p>CE EN 61000-3-2 2000, Class A</p> <p>Harmonic Current Emissions</p> <p>CE EN 61000 3-3 1995, Amendment A1: 2001</p> <p>Voltage Fluctuations and Flicker</p> <p>CE IEC 6100-4-2: 1995</p> <p>ESD Air Discharge 8kV. Contact Discharge 4kV.</p> <p>CE IEC 6100-4-3:1995</p> <p>Radiated Immunity (80-1000Mhz), 3V/m 80% A.M. by 1kHz</p> <p>CE IEC 6100-4-4:1995</p> <p>EFT/B: Immunity to electrical fast transients 1kV Power Leads, 0.5Kv Signals Leads</p> <p>CE IEC 6100-4-5:1995</p> <p>Immunity to conductive surges COM Mode; 2kV, Dif. Mode 1kV</p> <p>CE IEC 6100-4-6:1996</p> <p>Conducted immunity (0.15-80 MHz) 3VRMS 80% A.M. By 1kHz</p>

	CE IEC 6100-4-11:1994 Voltage Dips and Short Interruptions V reduc >95%, 30% >95% Duration 0.5per, 25per, 250per
MTBF*:	* The prediction was performed for 40°C Ambient temperature, GB Environmental condition. The reliability prediction was performed in accordance with Telcordia SR-332
LEDs	
LEDs:	Link /ACT : Turns on link , blinks on activity (green) Link: Turns on link any speed (green)
LEDs location:	LED is located on the PCB, visible via holes in the metal bracket holder
Connectors:	(1) SFP+ cage

Order Information

P/N	Description	Notes
PE210G1SPi9A-XR	Single Port SFP+ 10 Gigabit Ethernet PCI Express Server Adapte	X8 Gen2 , Based on Intel 82599ES, Low-profile, Support Direct Attached Copper cable, Support Silicom SFP+ approved transceiver. RoHS compliant
PE210G1SPi9A-SR	Single Port Fiber (SR) 10 Gigabit Ethernet PCI Express Server Adapter	X8 Gen2, Based on Intel 82599ES, Low-profile, on board support for Fiber SR, RoHS compliant
PE210G1SPi9A-LR	Single Port Fiber (LR) 10 Gigabit Ethernet PCI Express Server Adapter	X8 Gen2, Based on Intel 82599ES, Low-profile, on board support for Fiber LR, RoHS compliant
PE210G1SPi9A-SRD	Single Port Fiber (SX/SR) 1/10 Gigabit Ethernet PCI Express Server Adapter	X8 Gen2, Based on Intel 82599ES, Low-profile, on board support for Fiber SX/SR, RoHS compliant
PE210G1SPi9A-LRD	Single Port Fiber (SX/SR) 1/10 Gigabit Ethernet PCI Express Server Adapter	X8 Gen2, Based on Intel 82599ES, Low-profile, on board support for Fiber LX/LR,

		RoHS compliant
--	--	----------------

Model P/N -LP / -E

-LP: Assemble Low Profile Metal Bracket

-E: PXE Enable

*Advanced features may required driver development. Specifications details the 82599ES chips capabilities

1V1