

## 225TMA050M

AXIAL LEAD

Parts are RoHS compliant

Date code when parts became RoHS: 14



### ELECTRICAL SPECIFICATIONS

Capacitance: 2.2  $\mu$ F

Dissipation Factor: 0.12 Max at 120 Hz and 20°C

Temperature Range: -40°C to +105°C

Impedance: N/A

Tolerance: -20 %, +20 %

WVDC: 50 Volts DC

SVDC: 63 Volts DC

Ripple Current: 18 mA at 120 Hz and 105°C

Impedance Ratios: -25°C/20°C 2 and -40°C/20°C - 4

Leakage Current: .03CV or 4 $\mu$ A, whichever is greater  
4  $\mu$ A after 1 Minute

Load Life: 2000 hours at 105°C with 100 % of rated voltage and with 100 % of rated ripple current

Capacitance Change:  $\leq$ 20% of initial measured value

Dissipation Factor:  $\leq$ 200% of maximum specified value

Leakage Current:  $\leq$ 100% of maximum specified value

Frequency Multipliers:

50 HZ	120 HZ	400 HZ	1 KHZ	10 KHZ	100 KHZ
0.75	1	1.35	1.57	1.5	2

Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
2.23	2.17	1.9	2	1.75	1.75	1	0

### PHYSICAL DIMENSIONS

Diameter (D): 5 mm + 0.5 mm


Length (L): 13 mm + 1.5 mm

Coating: BlackPVC sleeving

Lead Wire Diameter (d): 0.6 mm +/- 0.05 mm

Lead Length: 35 mm +/- MIN mm

Lead Finish: Matte Tin



3757 W. Touhy Ave. Lincolnwood, IL 60712 (847) 675-1760 FAX (847) 673-2850  
Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, [www.illcap.com.hk](http://www.illcap.com.hk)  
© Copyright 2017 Illinois Capacitor. A division of Cornell Dubilier, All Rights Reserved