



Transmissive Type Photo-Interrupter

www.ct-micro.com

Features

- High reliability
- Gap width = 5mm
- Slit width = 0.5mm
- Good spectral matching to Si photo detector
- RoHS compliance

Description

The PIT5005T-CL is a transmissive type photo-interrupter which consist of an infrared emitting diode and an NPN silicon photo-transistor.


Applications

- Infrared sensor
- Printers
- Switch scanner

Package Outline



Schematic





Transmissive Type Photo-Interrupter

Absolute Maximum Rating at 25°C

Symbol	Parameters	Ratings	Units	Notes
T _{opr}	Operating Temperature	-25 ~ +80	°C	
T _{stg}	Storage Temperature	-40 ~ +85	°C	
T _{sol}	Soldering Temperature	260	°C	1
Emitter				
I _F	Continuous Forward Current	50	mA	
I _{FP}	Peak Forward Current	1	A	2
V _R	Reverse Voltage	5	V	
P _D	Power Dissipation at(or below) 25°C Free Air Temperature	75	mW	
Detector				
P _C	Collector Power Dissipation	75	mW	
I _C	Collector Current	20	mA	
B _{VCEO}	Collector-Emitter Voltage	30	V	
B _{VECO}	Emitter-Collector Voltage	5	V	

**Electro-Optical Characteristics** $T_A = 25^\circ\text{C}$ (unless otherwise specified)**Emitter Characteristics**

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V_F	Forward Voltage	$I_F=20\text{mA}$	-	1.20	1.60	V	2
		$I_F=100\text{mA}$	-	1.40	1.85		
		$I_F=1\text{A}$	-	2.60	4.00		
I_R	Reverse Current	$V_R=5\text{V}$	-	-	10	μA	
λ_p	Peak Wavelength	$I_F=20\text{mA}$	-	940	-	nm	

Detector Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
$B_{V_{CEO}}$	Collector-Emitter Breakdown	$I_C=100\mu\text{A}$	30	-	-	V	
$B_{V_{ECO}}$	Emitter-Collector Breakdown	$I_E=100\mu\text{A}$	5	-	-	V	
I_{CEO}	Dark Current	$V_{CE}=20\text{V}$	-	-	100	nA	

Transfer Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
I_C	Collect Current	$V_{CE}=5\text{V}, I_F=20\text{mA}$	0.5	10	-	mA	
$V_{CE(\text{sat})}$	C-E Saturation Voltage	$I_C=2\text{mA}, E_e=1\text{mW}/\text{cm}^2$	-	-	0.4	V	
t_r	Rise Time	$V_{CE}=5\text{V}, I_C=1\text{mA}$ $R_L=1\text{k}\Omega$	-	15	-	μs	
t_f	Fall Time		-	15	-		

Notes:1 : Soldering time ≤ 5 seconds.2 : I_{FP} Conditions--Pulse Width $\leq 100\mu\text{s}$ and Duty $\leq 1\%$.



Typical Characteristic Curves




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6



Typical Characteristic Curves




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11






Figure 12




Typical Characteristic Curves






Package Dimension All dimensions are in mm, unless otherwise stated.





Label Form Specification




Part no: CTM Production Number
 Serial no: Production Number
 Lot no: Lot number
 Q'ty: Packing Quantity
 Date Code: Manufacture Date
 Bin Code: Ic Ranks
 MADE IN CHINA: Production Place

Storage Condition

1. Do not open moisture proof bag before the products are ready to use.
2. The moisture barrier bag should be stored at 40°C and 90%R.H. max. before opening.
Shelf life of non-opened bag is 12 months after the bag sealing date.
3. After opening the moisture barrier bag floor life is 72h at 30°C/60%RH. max. Unused LEDs should be resealed into moisture barrier bag. (Refer to J-STD-020 Standard)
4. If the moisture absorbent material has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the J-STD-033 Standard conditions.



Reflow Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (T _{smin})	150°C
Temperature Max. (T _{smax})	200°C
Time (t _s) from (T _{smin} to T _{smax})	60-120 seconds
Ramp-up Rate (t _L to t _P)	3°C/second max.
Liquidous Temperature (T _L)	217°C
Time (t _L) Maintained Above (T _L)	60 – 150 seconds
Peak Body Package Temperature	260°C +0°C / -5°C
Time (t _P) within 5°C of 260°C	30 seconds
Ramp-down Rate (T _P to T _L)	6°C/second max
Time 25°C to Peak Temperature	8 minutes max.



Transmissive Type Photo-Interrupter

DISCLAIMER

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

CT MICRO ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICRO INTERNATIONAL CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*