



GLASS PACKAGE STEP RECOVERY DIODE

DESCRIPTION:


The **ASRD 700** Series of Step Recovery Diodes are Designed for General Purpose VCO and Sampler Applications.

FEATURES INCLUDE:

- Transition Time as Low as **70 pS**
- Hermetic Glass Package

MAXIMUM RATINGS

I_F	50 mA
V_R	UP TO RATED V_{BR}
P_{DISS}	290 mW
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +200 °C
θ_{JC}	0.6 °C /mW



STATIC ELECTRICAL CHARACTERISTICS $T_c = 25\text{ }^{\circ}\text{C}$

SYMBOL	TEST CONDITIONS			MINIMUM	TYPICAL	MAXIMUM	UNITS
V_{BR}	$I_R = 10\text{ }\mu\text{A}$		ASRD 703	70			V
			ASRD 715	50			
			ASRD 725	45			
			ASRD 733	25			
			ASRD 740	15			
			ASRD 751	15			
			ASRD 753	25			
C_{J6}	$V_R = 6\text{ V}$	$f = 1\text{ MHz}$	ASRD 703			6.0	pF
			ASRD 715			4.0	
			ASRD 725			2.0	
			ASRD 733			1.6	
			ASRD 740			0.6	
			ASRD 751			0.65	
			ASRD 753			0.4	




GLASS PACKAGE STEP RECOVERY DIODE

DYNAMIC ELECTRICAL CHARACTERISTICS $T_c = 25^\circ\text{C}$

SYMBOL	TEST CONDITIONS			MINIMUM	TYPICAL	MAXIMUM	UNITS
τ	$I_F = 10\text{ mA}$	$I_R = 6\text{ mA}$	ASRD 703	200			nS
			ASRD 715	100			
			ASRD 725	30			
			ASRD 733	10			
			ASRD 740	10			
			ASRD 751	10			
			ASRD 753	10			
T_t	$V_R = 7\text{ V}$	$I_F = 3\text{ mA}$	ASRD 703		400		pS
			ASRD 715		320		
			ASRD 725		160		
			ASRD 733		90		
			ASRD 740		75		
			ASRD 751		100		
			ASRD 753		95		

ORDERING INFORMATION:

ASRD 7XXB





GLASS PACKAGE STEP RECOVERY DIODE

CROSS REFERENCE

HP P/N	ASI P/N
5082-0151	ASRD 751
5082-0153	ASRD 753
5082-0803	ASRD 703
5082-0815	ASRD 715
5082-0825	ASRD 725
5082-0833	ASRD 733
5082-0840	ASRD 740