








RECOMMENDED PCB LAYOUT (COMPONENT SIDE VIEW)
EMPFOHLENER FUER LEITERPLATTE (BESTUECKUNGSSEITE)

TOL ±0.05 [.002] UNLESS NOTED



RECOMMENDED PANEL CUTOUT
EMPFOHLENER FRONTPLATTEN AUSSCHNITT



MAGNETICS SPECIFICATIONS @ 25°C

AUTO MDIX COMPATIBLE

URNS RATIO:

(P1-P2 : J1-J2) 1CT : 1 ±3%

(P3-P6 : J3-J6) 1CT : 1 ±3%

OCL (100KHz, 0.1Vrms, 8mA)

(P1-P2 : P3-P6) 350µH MIN

DCR (P1-P2, P3-P6) 1.1 OHMS MAX

INSERTION LOSS:

0.1 MHz - 100 MHz -1.1 dB MAX

RETURN LOSS:

0.5 MHz - 30 MHz -18 dB MIN

40 MHz -15.5 dB MIN

50 MHz -13.6 dB MIN

60 MHz - 80 MHz -12 dB MIN

CROSSTALK (0.1 MHz - 100 MHz) -40 dB TYP

COMMON MODE REJECTION

0.1 MHz - 30 MHz: -50 dB TYP

30 MHz - 60 MHz: -40 dB TYP

60 MHz - 100 MHz: -35 dB TYP

ISOLATION: 1500 Vrms

MATERIALS AND FINISH

HOUSING: GLASS FILLED POLYESTER UL 94 V-0 BLACK

SHIELDING: Cu ALLOY, PLATED WITH Ni

CONTACTS: PHOSPHOR BRONZE

CONTACT FINISH: Au, 0.8 µm (30 µin) OVER Ni


TERMINAL FINISH: SnPb

MECHANICAL CHARACTERISTICS

DURABILITY: 1000 MATING CYCLES

OPERATING TEMPERATURE: -40°C TO 85°C

ELECTRICAL SCHEMATIC - 10/100 BASE TX - H3D01 EXTENDED TEMPERATURE RANGE



NOTE 1: SIDE SHIELD TABS IN REAR 3.05mm (R)

NOTE 2: PANEL GROUND FLANGES BOTH SIDES AND TOP (GF5)

Information:		Tolerances		Scale 2:1	Class. No. -
All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation MOD JACK - MJIM 8C7T, 1X1, INTEGRATED MAGNETICS	
		www.ERNI.com		203338	
b	02JUL04	Date		MAXMJ	
Index					