

LR2-D

~14° diffused spot beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.


TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.6 mm
Height	14.8 mm
Fastening	tape, pin
Colour	white
Box size	480 x 280 x 300 mm
Box weight	9.6 kg
Quantity in Box	1680 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:



Component	Type	Material	Colour
LXP2-D	Lens	PMMA	clear
LR2-ES-LH1-HLD	Holder	PC	white
HEIDI-TAPE	Tape	PU tape	black



PHOTOMETRIC DATA (MEASURED):





LED XP-L
FWHM 17.0°
Efficiency 92 %
Peak intensity 6.910 cd/lm
Required components:




LED LUXEON Rebel ES
FWHM 14.0°
Efficiency 92 %
Peak intensity cd/lm
Required components:



LED LUXEON T
FWHM 14.0°
Efficiency 94 %
Peak intensity 7.000 cd/lm
Required components:



LED LUXEON TX
FWHM 13.0°
Efficiency 90 %
Peak intensity 11.280 cd/lm
Required components:





PHOTOMETRIC DATA (MEASURED):




LED LUXEON Z ES
FWHM 10.0°
Efficiency 90 %
Peak intensity 15.400 cd/lm
Required components:



LED NVSxx19B/NVSxx19C
FWHM 15.0°
Efficiency 92 %
Peak intensity 6.500 cd/lm
Required components:




LED Oslon Square EC
FWHM 12.0°
Efficiency 91 %
Peak intensity 11.100 cd/lm
Required components:




PHOTOMETRIC DATA (SIMULATED):



LED XQ-E
FWHM 9.0°
Efficiency 92 %
Peak intensity 28.000 cd/lm
Required components:



LED LUXEON H50-2
FWHM 12.5°
Efficiency 93 %
Peak intensity 12.600 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salu, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)