N-Channel Enhancement Mode Power MOSFET

MTE130N20J3

BV_{DSS}	200V
I_D@V_{GS}=10V, T_C=25°C	18A
I_D@V_{GS}=10V, T_A=25°C	1.9A
$R_{DSON(TYP)}$ @ V_{GS}=10V, I_D=9A	156mΩ

Features

- Low Gate Charge
- Simple Drive Requirement
- Fast Switching Characteristic
- Pb-free lead plating and halogen-free package

Symbol

MTE130N20J3



G：Gate D：Drain S：Source

Outline

TO-252(DPAK)

G D S

Ordering Information

Device	Package	Shipping
MTE130N20J3-0-T3-G	TO-252 (Pb-free lead plating and halogen-free package)	2500 pcs / Tape & Reel



Environment friendly grade : S for RoHS compliant products, G for RoHS compliant and green compound products

Packing spec, T3 : 2500 pcs / tape & reel, 13” reel

Product rank, zero for no rank products

Product name

Absolute Maximum Ratings (T_C=25°C, unless otherwise noted)

Parameter		Symbol	Limits	Unit
Drain-Source Voltage		V_{DS}	200	V
Gate-Source Voltage		V_{GS}	±20	
Continuous Drain Current @ T_C=25°C (Note 1)		I_D	18	A
Continuous Drain Current @ T_C=100°C (Note 1)			13	
Pulsed Drain Current (Note 3)		I_{DM}	30	
Continuous Drain Current @ T_A=25°C (Note 4)		I_{DSM}	1.9	
Continuous Drain Current @ T_A=70°C (Note 4)			1.5	
Avalanche Current (Note 3)		I_{AS}	3	
Avalanche Energy @ L=1mH, I_D=3A, V_{DD}=50V (Note 3)		E_{AS}	4.5	mJ
Power Dissipation	T_C=25°C (Note 1)	P_D	125	W
	T_C=100°C (Note 1)		62.5	
Power Dissipation	T_A=25°C (Note 2)	P_{DSM}	2	W
	T_A=70°C (Note 2)		1.3	
Operating Junction and Storage Temperature		Tj, Tstg	-55~+175	°C

Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-case, max	$R_{th,j-c}$	1.2	°C/W
Thermal Resistance, Junction-to-ambient, max, t≤10s (Note 2)	$R_{th,j-a}$	62.5	°C/W
Thermal Resistance, Junction-to-ambient, max (Note 4)		90	°C/W

Note : 1. The power dissipation P_D is based on $T_{J(MAX)}$=175°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

2. The value of $R_{\theta JA}$ is measured with the device mounted on 1 in² FR-4 board with 2 oz. copper, in a still air environment with T_A=25°C. The power dissipation P_{DSM} is based on $R_{\theta JA}$ and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.

3. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=175°C. Ratings are based on low frequency and low duty cycles to keep initial T_J=25°C.

4. When mounted on the minimum pad size recommended (PCB mount), t≤10s.

Characteristics (T_C=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV_{DSS}	200	-	-	V	V_{GS}=0V, I_D=250μA
$\Delta BV_{DSS}/\Delta Tj$	-	0.2	-	V/°C	Reference to 25°C, I_D=250μA
$V_{GS(th)}$	2.0	-	4.0	V	V_{DS} = V_{GS}, I_D=250μA
G_{FS}	-	12	-	S	V_{DS} =10V, I_D=9A
I_{GSS}	-	-	±100	nA	V_{GS}=±20V
I_{DSS}	-	-	1	μA	V_{DS} =180V, V_{GS} =0V
	-	-	10		V_{DS} =180V, V_{GS} =0V, Tj=125°C
*$R_{DS(ON)}$	-	156	195	mΩ	V_{GS} =10V, I_D=9A
Dynamic					
*Qg	-	19	-	nC	V_{DS}=160V, I_D=18A, V_{GS}=10V
*Qgs	-	5	-		
*Qgd	-	7.2	-		
*$t_{d(ON)}$	-	12.6	-	ns	V_{DS}=100V, I_D=18A, V_{GS}=10V, R_G=6Ω
*tr	-	35	-		
*$t_{d(OFF)}$	-	27.6	-		
*t_f	-	14.6	-		
Ciss	-	813	-	pF	V_{GS}=0V, V_{DS}=25V, f=1MHz
Coss	-	85	-		
Crss	-	36	-		
Source-Drain Diode					
*I_S	-	-	18	A	
*I_{SM}	-	-	30		
*V_{SD}	-	0.86	1.2	V	I_S=18A, V_{GS}=0V
*trr	-	80	-	ns	I_F=18A, V_{GS}=0, dI_F/dt=100A/μs
*Qrr	-	245	-	nC	

*Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%

Recommended soldering footprint



Typical Characteristics

Typical Output Characteristics



Brekdown Voltage vs Ambient Temperature



Static Drain-Source On-State resistance vs Drain Current



Reverse Drain Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage



Drain-Source On-State Resistance vs Junction Tempearture



Typical Characteristics(Cont.)

Capacitance vs Drain-to-Source Voltage



NormalizedThreshold Voltage vs Junction Tempearture



Forward Transfer Admittance vs Drain Current



Gate Charge Characteristics



Maximum Safe Operating Area



Maximum Drain Current vs Case Temperature



Typical Characteristics(Cont.)

Typical Transfer Characteristics



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curves



Reel Dimension



Carrier Tape Dimension



Notes:
1. 10 sprocket hole pitch cumulative tolerance ±0.2.
2. Camber not to exceed 1mm in 100mm.
3. Material: conductive black polystyrene, antistatic coated : 10^{5} Ω/□~ 10^{11} Ω/□ unit : mm

Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (Tsmax to Tp)	3°C/second max.	3°C/second max.
Preheat −Temperature Min(T_S min) −Temperature Max(T_S max) −Time($t_{s\ min}$ to $t_{s\ max}$)	 100°C 150°C 60-120 seconds	 150°C 200°C 60-180 seconds
Time maintained above: −Temperature (T_L) − Time (t_L)	 183°C 60-150 seconds	 217°C 60-150 seconds
Peak Temperature(T_P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

TO-252 Dimension





3-Lead TO-252 Plastic Surface Mount Package
CYStek Package Code: J3

Style: Pin 1.Gate 2.Drain 3.Source 4.Drain

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.087	0.094	2.200	2.400	e	0.086	0.094	2.186	2.386
A1	0.000	0.005	0.000	0.127	e1	0.172	0.188	4.372	4.772
B	0.039	0.048	0.990	1.210	H	0.163	REF	4.140	REF
b	0.026	0.034	0.660	0.860	K	0.190	REF	4.830	REF
b1	0.026	0.034	0.660	0.860	L	0.386	0.409	9.800	10.400
C	0.018	0.023	0.460	0.580	L1	0.114	REF	2.900	REF
C1	0.018	0.023	0.460	0.580	L2	0.055	0.067	1.400	1.700
D	0.256	0.264	6.500	6.700	L3	0.024	0.039	0.600	1.000
D1	0.201	0.215	5.100	5.460	P	0.026	REF	0.650	REF
E	0.236	0.244	6.000	6.200	V	0.211	REF	5.350	REF

Notes: 1.Controlling dimension: millimeters.
2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead : Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek ***semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.***
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.