



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date:

Product Name: SAW Resonator 418 MHz SMD 5X5 mm

TST Parts No.: TC0117A

Customer Parts No.: _____

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Vincent Liu

Approval by: _____ Francis Chen

Date: _____ 2003/6/18



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Resonator 418 MHz

MODEL NO.: TC0117A

REV. NO.:1

A. FEATURES:

1. 1-Port Resonator.

B. MAXIMUM RATING:


1. Input Power Level: 0 dBm
2. DC voltage: 12 V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -40°C to +85°C

C. ELECTRICAL CHARACTERISTICS:

Characteristic	Units	Minimum	Typical	Maximum
Center frequency Fr	MHz	417.925	418	418.075
Insertion Loss IL	dB		0.9	2.0
Equivalent Elements				
Motional capacitance C1	fF	-	2.19	-
Motional inductance L1	μH	-	66.11	-
Motional resistance R1	Ohm	-	12.68	-
Parallel capacitance Co	pF	-	3.65	-
Temp.coeff.	ppm/c*2	-	0.032	-
Turnover To	deg.C	20	-	50
Package size		SMD 5X5X1.4mm		


RoHS Compliant
Lead free
Lead-free soldering

D. OUTLINE DRAWING:




E. EQUIVALENT CIRCUIT:


One-Port Resonator:



F. FREQUENCY CHARACTERISTICS:




G. TEST CIRCUIT:



H. PACKING:

1. REEL DIMENSION



2.TAPE DIMENSION

